



Title	NEAR: A Partner to Explain Any Factorised Recommender System
Authors(s)	Ouyang, Sixun, Lawlor, Aonghus
Publication date	2019-06-12
Publication information	Ouyang, Sixun, and Aonghus Lawlor. "NEAR: A Partner to Explain Any Factorised Recommender System." ACM, June 12, 2019. https://doi.org/10.1145/3314183.3323457 .
Conference details	UMAP'19: 27th Conference on User Modeling, Adaptation and Personalization, Larnaca, Cyprus, 9-12 June 2019
Publisher	ACM
Item record/more information	http://hdl.handle.net/10197/10861
Publisher's statement	© ACM, 2019. This is the author's version of the work. It is posted here by permission of ACM for your personal use. Not for redistribution. The definitive version was published in UMAP'19 Adjunct Adjunct Publication of the 27th Conference on User Modeling, Adaptation and Personalization (2019) http://doi.acm.org/10.1145/3314183.3323457
Publisher's version (DOI)	10.1145/3314183.3323457

Downloaded 2026-05-01 23:42:04

The UCD community has made this article openly available. Please share how this access benefits you. Your story matters! (@ucd_oa)



© Some rights reserved. For more information

NEAR: a partner to explain any factorised recommender system

Sixun Ouyang

Insight Centre for Data Analytics
University College Dublin, Ireland
sixun.ouyang@insight-centre.org

Aonghus Lawlor

Insight Centre for Data Analytics
University College Dublin, Ireland
aonghus.lawlor@insight-centre.org

ABSTRACT

Many explainable recommender systems construct explanations of the recommendations these models produce, but it continues to be a difficult problem to explain to a user why an item was recommended by these high-dimensional latent factor models. In this work, We propose a technique that joint interpretations into recommendation training to make accurate predictions while at the same time learning to produce recommendations which have the most explanatory utility to the user. Our evaluation shows that we can jointly learn to make accurate and meaningful explanations with only a small sacrifice in recommendation accuracy. We also develop a new algorithm to measure explanation fidelity for the interpretation of top- n rankings. We prove that our approach can form the basis of a universal approach to explanation generation in recommender systems.

CCS CONCEPTS

• **Information systems** → **Learning to rank; Recommender systems; Interpretation**; • **Computing methodologies** → *Feature selection*;

KEYWORDS

Recommender systems, Learn to rank, Interpretation, Explanations

ACM Reference Format:

Sixun Ouyang and Aonghus Lawlor. 2019. NEAR: a partner to explain any factorised recommender system. In *27th Conference on User Modeling, Adaptation and Personalization Adjunct (UMAP'19 Adjunct)*, June 9–12, 2019, Larnaca, Cyprus. ACM, New York, NY, USA, 3 pages. <https://doi.org/10.1145/3314183.3323457>

1 INTRODUCTION

Latent factorisation methods continue to receive substantial attention in a long history in recommender system field [3, 8, 13, 16, 17]. At the same time, the process of explaining the resulting recommendations has also received considerable attention from both academia and industry. Rating prediction has been addressed through various approaches [1, 7, 10, 14, 15], however, the top- n ranking explanation is a tough problem which has not been thoroughly tackled.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

UMAP'19 Adjunct, June 9–12, 2019, Larnaca, Cyprus

© 2019 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM ISBN 978-1-4503-6711-0/19/06...\$15.00
<https://doi.org/10.1145/3314183.3323457>




Figure 1: Processes of NEAR

On the other hand, general explaining recommender systems leverage the importance of observable attributes to make interpretations [12, 14, 15]. Nevertheless, they all aim to explain a particular domain, and are difficult to extend to other realms. As such, we target on providing explanations on latent factors, the basis of recommender systems, to form a universal foundation of recommendation explanations. Specifically, our method plays as the extensive model that joint interpretations into recommendation training to produce top- n ranked lists that provide optimal personalised explanations, where this procedure we named as *explain training*.

In this paper, we propose a robust method Native Explanation System for Agnostic Recommendation (NEAR), a method for training a recommender system with joint explanations. Our experiments show that by sacrificing a little precision, the joint system is able to supply accurate recommendations alongside convincing explanations. We also introduce a new explanation fidelity algorithm which has interesting applications for evaluating any model for explaining a ranked list.

2 RELATED WORK

From the early days of recommender systems, many works have explored the utility of explanations. Herlocker *et al.*[5] studied various interpretations leveraging distinct data types and visualisation styles on collaborative filtering tasks, and concluded that these approaches lead to users paying more attention to the value of recommendation explanations. Many works interpret recommendations in different ways. Vig *et al.*[15] used community tags to explain related recommendations. Costa *et al.*[?] indicated an alternative approach, machine-generated reviews, to offer explanations for recommendations. Hoeve *et al.*[14] outlined an algorithm that uses global point of interests of the factors to construct explanations, which is called LISTwise ExplainNer (LISTEN). Although these methods successfully addressed many explanation approaches, there are only few works which attempt to fully explain a top- n recommendation. In this paper, we focus on joint explanations into recommendation training as a closed circuit and offer reliable explanations for top- n recommendations.




Figure 2: Test RMSE loss of explain training and non-explain training on 2 datasets from different domains.

3 NATIVE EXPLAINER FOR AGNOSTIC RECOMMENDATION

NEAR consists of two parts: a training phase and an explain phase. The training phase, aforementioned *explain training*, is the primary section that we alternate between a training step of the recommender system and NEAR to ensure explainable and accurate prediction, while the explain phase is used to generate latent factor based interpretations for top- n rank. The full process is shown in Fig. 1. The training phase starts by disturbing the user embeddings which are the input to the factorisation model. Once the perturbation is applied, we use a factor selection method [14] to identify the most salient factor in the recommendation set, mimicking the process of a user selecting the item with the most relevant factor. In this way, the factors which are found to be the most salient by the factor selection method, are associated with more relevant items in the top- n recommendations. Similar to training phase, explain phase employ a leave one out disturb method [12] at first step. Then we feed the perturbed embeddings into *lasso* regression to get the weights of each factor. Because *lasso* leverages the importance of the factors by their weights, we denote these weights as the contributions of each factor.

4 EXPERIMENTS

Our experiments are conducted on 2 real-world review datasets from different domains: Movielens [4], and Beeradvocates [9], and on SVD++ [6], to evaluate against regular training.

4.1 Is NEAR reliable?

In this section, we measure the recommendation performance by Root Mean Square Error (RMSE) [2] on test set. Fig 2 illustrates the performance comparison of explain training and non-explain training. These results highlight a number of interesting features of NEAR. First, the non-explain training model performs slightly better than the with-explain method, which indicates a minor trade-off in accuracy by jointly learning the personalised explanations. On the other hand, the with-explain method converges much quicker and reach a similar minimum RMSE to the non-explain methods. This demonstrates that the with-explain methods are both accurate and precise and provide relevant and persuasive recommendations to users.

4.2 Can NEAR contribute to top- n explanation?

To explain a top- n list, we initially compute the overall contributions of each users' factor through the explain phase. Then for each




Figure 3: Recommendation explanation fidelity results. Evaluated on NDCG@ k and top m users' factors.

factor, we re-employ the leave one out method in explain phase to create a perturbed embedding, and further making a new top- n recommendation. To do so, these top- n is purely based on a specific factor, so that we can leverage how critical of a factor to the top- n list. We develop the explanation fidelity algorithm [11] which shown in Eq. 1. This fidelity algorithm counts the number of top- n instances where the average NDCG@ K of top m factors is greater than that of other factors. The primary advantage is that we avoid bias in the results by incorporating weights of many factors instead of just one.

$$\mathcal{F}_{k,m} = \frac{\sum_{r=1}^R \overline{NDCG@k(f_r \in m)} > \overline{NDCG@k(f_r \notin m)}}{R} \quad (1)$$

Evaluation on top- n explanation is demonstrated in Fig. 3, where the x-axis denotes factor ids which is sorted in decreasing order by their contributions, while the y-axis is the explanation fidelity. According to this, several observations can be made: (1) explanation fidelity decreased as m increased, which indicates NEAR returns the factors in the correct order; (2) explanation fidelity also declined along with increasing k . This is an expected outcome because it is impractical to maintain the same fidelity for different k values by the same size of factors; (3) NEAR is able to sustain explanation fidelity when trying to interpret longer top- k recommendation ranked lists, as there are only minuscule decrements between NDCG@5 and NDCG@10 on both of the experiments.

5 CONCLUSIONS

In this paper, we proposed NEAR, a robust explanation method for any latent factorised recommendation system. We introduced a cost function of explanation-training and argued this training method is crucial for personalisation. We showed that NEAR can present accurate and meaningful explanations without sacrificing a lot of precision in the recommendations. Concerning top- N explanation, we demonstrated a new interpretation fidelity algorithm and confirmed NEAR can produce the substantial foundation for explaining any top- N recommendation list. The NEAR method comprises many features which make it useful for general latent factor models, and future work will explore some extensions of the method, applying it to larger review domains, applying it to non-review based datasets, and further improving the evaluation.

6 ACKNOWLEDGMENTS

This work is supported by Science Foundation Ireland through the Insight Centre for Data Analytics under grant number SFI/12/RC/2289

REFERENCES

- [1] Mustafa Bilgic and Raymond J Mooney. 2005. Explaining recommendations: Satisfaction vs. promotion. In *Beyond Personalization Workshop, UII*, Vol. 5. 153.
- [2] Chong Chen, Min Zhang, Yiqun Liu, and Shaoping Ma. 2018. Neural A entional Rating Regression with Review-level Explanations. (2018).
- [3] Paul Covington, Jay Adams, and Emre Sargin. 2016. Deep neural networks for youtube recommendations. In *Proceedings of the 10th ACM Conference on Recommender Systems*. ACM, 191–198.
- [4] F Maxwell Harper and Joseph A Konstan. 2016. The movielens datasets: History and context. *Acm transactions on interactive intelligent systems (tiis)* 5, 4 (2016), 19.
- [5] Jonathan L Herlocker, Joseph A Konstan, and John Riedl. 2000. Explaining collaborative filtering recommendations. In *Proceedings of the 2000 ACM conference on Computer supported cooperative work*. ACM, 241–250.
- [6] Yehuda Koren. 2008. Factorization meets the neighborhood: a multifaceted collaborative filtering model. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*. ACM, 426–434.
- [7] Emanuel Lacic, Dominik Kowald, and Elisabeth Lex. 2016. High Enough?: Explaining and Predicting Traveler Satisfaction Using Airline Reviews. In *Proceedings of the 27th ACM Conference on Hypertext and Social Media*. ACM, 249–254.
- [8] Daniel D Lee and H Sebastian Seung. 2001. Algorithms for non-negative matrix factorization. In *Advances in neural information processing systems*. 556–562.
- [9] Julian John McAuley and Jure Leskovec. 2013. From amateurs to connoisseurs: modeling the evolution of user expertise through online reviews. In *Proceedings of the 22nd international conference on World Wide Web*. ACM, 897–908.
- [10] Khalil Muhammad, Aonghus Lawlor, Rachael Rafter, and Barry Smyth. 2015. Great explanations: Opinionated explanations for recommendations. In *International Conference on Case-Based Reasoning*. Springer, 244–258.
- [11] Georgina Peake and Jun Wang. 2018. Explanation Mining: Post Hoc Interpretability of Latent Factor Models for Recommendation Systems. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. ACM, 2060–2069.
- [12] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. Why should i trust you?: Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*. ACM, 1135–1144.
- [13] Gilbert Strang. 1993. The fundamental theorem of linear algebra. *The American Mathematical Monthly* 100, 9 (1993), 848–855.
- [14] Maartje ter Hoeve, Anne Schuth, Daan Odijk, and Maarten de Rijke. 2018. Faithfully Explaining Rankings in a News Recommender System. *arXiv preprint arXiv:1805.05447* (2018).
- [15] Jesse Vig, Shilad Sen, and John Riedl. 2009. Tagsplanations: explaining recommendations using tags. In *Proceedings of the 14th international conference on Intelligent user interfaces*. ACM, 47–56.
- [16] Lu Wang, Wei Zhang, Xiaofeng He, and Hongyuan Zha. 2018. Supervised reinforcement learning with recurrent neural network for dynamic treatment recommendation. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. ACM, 2447–2456.
- [17] Lei Zheng, Vahid Noroozi, and Philip S Yu. 2017. Joint deep modeling of users and items using reviews for recommendation. In *Proceedings of the Tenth ACM International Conference on Web Search and Data Mining*. ACM, 425–434.