Research Repository UCD

Title	Geotechnical properties of Dublin boulder clay
Authors(s)	Long, Michael (Michael M.), Menkiti, Christopher O.
Publication date	2007-09
Publication information	Long, Michael (Michael M.), and Christopher O. Menkiti. "Geotechnical Properties of Dublin Boulder Clay" 57, no. 7 (September, 2007).
Publisher	Institution of Civil Engineers
Item record/more information	http://hdl.handle.net/10197/3141
Publisher's statement	This is an electronic version of an article published in Géotechnique, 57 (7): 595-611, available online at: http://dx.doi.org/10.1680/geot.2007.57.7.595 .
Publisher's version (DOI)	10.1680/geot.2007.57.7.595

Downloaded 2023-04-07T10:52:29Z

The UCD community has made this article openly available. Please share how this access benefits you. Your story matters! (@ucd_oa)

© Some rights reserved. For more information

Title of Paper:	Geotechnical properties of Dublin boulder clay
Name of Author No. 1:	Michael Long, BE, MEngSc, Ph.D., CEng, MICE, MIEI
Name of Author No. 2:	Christopher O. Menkiti, BSc, MSc, Ph.D
Position / affiliation of Author No. 1:	Senior Lecturer, School of Architecture, Landscape and Civil Engineering, University College Dublin, Earlsfort Terrace, Dublin 2, Ireland
Position / affiliation of Author No. 2:	Associate Director, Geotechnical Consulting Group, London, UK
Address for correspondence:	Michael Long, School of Architecture, Landscape and Civil Engineering, University College Dublin, Earlsfort Terrace, Dublin 2, Ireland.
Other contact details:	Phone: +353-1-7167333 Fax: +353-1-7167399 e-mail: Mike.Long@ucd.ie
Date Paper Written:	March 2006
Date Paper Revised:	December 2006

SYNOPSIS

Geotechnical characteristics of Dublin Boulder Clay (DBC) based on detailed site investigation and site experience from some recent large projects in Dublin are presented. This paper attempts to synthesise available information in parallel with recent work by Skipper et al (2005), who provide an updated understanding of the geology of the DBC. Having assessed the effects of sampling disturbance, the paper characterises the various formations and sub-units of the DBC. The interpreted material behaviour is related to observed engineering performance. It was found from the behaviour of earth retained structures that intact, clayey, DBC formations are 2 to 3 times stiffer than assessed from high quality laboratory tests on block samples. DBC is shown to be significantly stiffer than other well-characterised tills. Relatively inexpensive Multi Channel Surface Wave techniques (MASW) can give very reliable estimates of in situ small strain stiffness. High undrained triaxial compression strengths were measured and it appears that simple UU tests on high quality specimens give good results. Significant strength anisotropy was suggested by undrained triaxial extension strengths that were only 30% to 50% of the triaxial compression strengths. Field horizontal permeability values of the intact clayey till units have a representative mean of about 10^{-9} m/s and when compared to laboratory values suggest that the material may exhibit some degree of anisotropy of permeability. Overall, the measured engineering parameters for the DBC are favourable for many construction projects. Further work is required in order to understand the in situ horizontal stress profile and the stiffness anisotropy of the till.

KEYWORDS: Glacial soils, In situ testing, laboratory tests, site investigation, strength, stiffness.

INTRODUCTION

This paper gives geotechnical characteristics of the various formations comprising the Dublin Boulder Clay (DBC), based on experience of a number of large projects in Dublin the capital city of the Republic of Ireland. DBC is the primary superficial deposit overlying bedrock. As a result of the recent boom in the Irish economy, a number of large-scale civil engineering projects have been completed or substantially advanced. From an associated wealth of borehole investigations, in-situ tests, laboratory tests, excavation exposures and monitored field performance, these projects have provided much more detailed information on the superficial deposits in Dublin.

Technical data are now available from a concentration of such projects in Dublin, but these are not in the public domain and have not been interpreted and correlated on a (geological) formation-level scale. There are significant economic benefits in understanding the characteristics of the DBC as it underlies much of the city, see Figure 1. A parallel study is reported by Skipper et al (2005), which provides a more detailed understanding of the geology of the DBC, and serves as a backdrop to this paper.

Much of the data are from the Dublin Port Tunnel Project (DPT, Site 1), which has been augmented by information from other important developments, as listed below and shown in Figure 1.

Site 1: Dublin Port Tunnel

The central part of the DPT project comprises 12m external diameter twin bored tubes, with lengths of cut and cover tunnel at either end. The project involves the excavation of about 1.5 million cubic metres of soil and rock. Although project wide information is

considered, focus in this paper is placed on experience gained at the northern cut and cover section and shaft WA2, where excavations were carried out in the superficial deposits to about 25m depth, see Figure 1. Further details of the project and a review of case histories associated with it are given by Long et al. (2003), Menkiti et al (2004) and Milligan et al. (2006).

Other sites

A summary of the other sites considered and the data obtained are given on Table 1 and the site locations are shown on Figure 1. Note that the sites span an area approximately 10 km east-west and 12 km north-south confirming the geographical dominance of DBC in the area.

SPECIAL SAMPLING METHODS

Undisturbed Block Samples

Undisturbed pushed-in block samples were recovered from the DPT project. The block samples were taken using 300 mm or 350 mm cubical, thin walled steel samplers, with a 20° or 45° outside angle cutting edge, respectively and 9 mm thick sidewalls. These sampler dimensions give an area ratio (AR) of 10% to 12% [where $AR = (A_e - A_c) / A_c$ and A_e and A_c are the external and internal areas of the cutting shoe]. Only the central portions of the block samples were tested.

Geobore 'S' Rotary Coring

High quality samples were recovered, at several of the study sites, using this wire-line, triple tube rotary coring technique with polymer flush to optimise sample recovery. The wire-line assembly allows the sample to be retrieved immediately after coring and minimises the duration the sample is in contact with the flushing medium. In general,

95% core recovery was achieved with experienced drilling crews. Samples for laboratory tests were cut from the recovered cores and sealed with wax and cling film immediately after core recovery. At the DPT site those obtained in 2000 and 2002/2003 were by Geobore-S boring and the 1996 sampling was by a mixture of conventional double and triple tube core barrels.

GEOLOGICAL SETTING

Since a detailed description of the geology is given by Skipper et al. (2005), only a brief summary is provided here. The area of outcrop of the DBC is indicated in Figure 1, based on the Geological Survey of Ireland 1:50,000 scale soils map of Dublin. Note that this sketch map is not intended to be a definite geological map of Dublin but merely aims to show the location of the study sites and the prevalence of DBC in the area. In this zone, generally a thin layer of recent deposits of made ground or loess overlies DBC – a lodgement till deposited under ice sheets more than 1 km thick. The following distinct formations of the Dublin Boulder Clay have been identified by Skipper and co-workers based on work for the DPT project. As well as at the DPT site all four units have been identified at the Mater hospital (Figure 1). South of the River Liffey the third unit (LBrBC) appears to be absent. Further work is required to define distribution of the various units throughout the city.

Upper Brown Boulder Clay (UBrBC)

This is the weathered uppermost formation of the Dublin Boulder Clay. It is a 2m to 3m thick stiff to very stiff, brown, slightly sandy clay, with rare silt / gravel lenses and some rootlets, particularly in the upper metre. Farrell et al. (1995a) have confirmed that this material is the weathered zone of the underlying Upper Black Boulder Clay (UBkBC)

and that oxidation has produced the brown colour. The UBrBC represents a complex pedogenic horizon, which developed during a period of climate warming and glacial retreat after the deposition of the UBkBC.

Upper Black Dublin Boulder Clay (UBkBC)

This is a very stiff, dark grey, slightly sandy clay, with some gravel and cobbles. It is typically 4 m to 12 m thick. Rare, sub-vertical, rough and very tightly closed fissures spaced at 0.5 m to 0.75m were observed at some locations. Considerable mechanical effort was required to excavate the material, which tended to break into peds of similar dimensions. In the DPT project, these fissures were observed to be so tightly closed in the in situ material that they could not be seen in borehole cores, and were only obvious in excavated material and slopes due to the manner in which the material broke apart. Thin horizontal cobble lines of striated, faceted cobbles are frequently seen, which persist laterally for tens of metres before terminating abruptly. These are associated with the sub-horizontal discontinuities and possibly with shear planes within the lodgement till. Occasional, small gravel lenses occur along the cobble lines and these may be water bearing. It was observed during the DPT project that the gravel lenses and cobble lines constitute a network that appeared to be hydraulically interconnected in some areas and hydraulically isolated elsewhere.

Lower Brown Dublin Boulder Clay (LBrBC)

The Lower Brown DBC exists as a 5 m to 9 m thick hard, brown, silty clay, with gravel, cobbles and boulders. It has previously been called the “sandy boulder clay” as it is similar to but siltier than the UBkBC above. The unit contains more frequent, larger and

more complex silt / gravel lenses and cobble lines than the UBkBC. At the DPT site a continuous 2 m thick layer of silty sand / fine gravel exists within the unit at 10 m to 16 m depth.

Lower Black Dublin Boulder Clay (LBkBC)

The lower black DBC is a patchy layer of hard slightly sandy gravelly clay with an abundance of boulders. It is generally more plastic to the touch than the LBrBC. Its thickness does not exceed 4 m and is typically less than 2 m.

Soil fabric

In general, the intact clayey DBC formations comprise a dense packing of well-graded material, leading to a high bulk unit weight, low pore sizes and hence low permeability. This is consistent with the in situ development of suctions following stress relief, as reported by Long et al. (2004). Figure 2 shows a typical view of the upper black boulder clay (UBkBC), as observed under a scanning electron microscope at a magnification of 3500. The view is typical of the clayey formations of DBC. It can be seen that the clay and silt sized fractions comprise both platy and rotund particles.

BASIC MATERIAL PARAMETERS

Stratigraphy and groundwater

At the Port Tunnel site all four units of the DBC were present, as shown on Figure 3. Also shown on this plot are piezometric pressures measured in piezometers and standpipes whose tips were located at various depths. It can be seen that the measured pressures correspond to approximately hydrostatic conditions with a groundwater table about 2 m below ground level.

Moisture content and bulk density

The distribution of moisture content and bulk density with depth for the DPT site is also shown on Figure 3 and average values of all the data points are summarised on Table 2. Overall both moisture content and bulk density values are uniform with depth. A detailed assessment of the data reveals that average moisture content in the UBrBC is somewhat larger than for the other layers, with a corresponding slightly smaller bulk density. The UBkBC has the lowest moisture content and highest bulk density. Values for the LBrBC and the LBkBC are very similar. The water content of the stone fraction alone was found to be negligible, indicating that all the soil moisture is retained in the soil matrix.

The formation most commonly encountered in normal excavations or at foundation level in Dublin is the UBkBC and the values given in brackets on Table 2 for this material are typical values reported by Lehane and Simpson (2000). It can be seen that the DPT site data fall within the reported general range.

SOIL COMPOSITION

Particle size distribution

Particle size distribution curves for the four formations at the DPT sites are shown on Figure 4. Perhaps the most uniform material is the UBkBC. Data for this site compare very well with the range of values for Dublin black boulder clay presented by Orr and Farrell (1996), see Figure 4, and with the typical values given by Lehane and Simpson (2000), see Table 2. The curves represent well-graded material and are typical of those of a lodgement till (Hanrahan, 1977 and Trenter, 1999). The single available test for the UBrBC confirms that its composition is more or less identical to the upper black boulder clay. Composition of both the LBrBC and LBkBC is more variable. For details of the sub-layers within the LBrBC, the reader is referred to Skipper et al. (2005).

Also shown on Figure 4 are some curves for various layers and lenses within the main strata at the DPT site, but which are typical of those encountered elsewhere. These include lenses of relatively gravelly material in the UBkBC. These are often composed of distinct gravel / silt units and may fine up or down. Deltaic sequences of sands, silts and clays are found in the LBrBC.

In general the quantity of the various constituents are relatively constant with depth. Based on the average values, quoted on Table 2 it can be seen that there is some tendency for the quantity of clay and silt to increase with depth. Except for the LBkBC boulder clay, the sand content remains relatively constant with depth and the gravel content reduces with depth.

Mineralogy

X-ray diffraction studies were carried out at the National History Museum, London on samples of each of the four formations. Specimens tested had particle size less than 2 μm . On average 76% of these specimens were composed of clay minerals. Quartz, calcite and traces of amorphous iron made up the remainder. The clay minerals comprise the following: a small fraction of kaolinite (i.e. 4% to 14% of the clay minerals), with the balance being split between the illite (28% - 43% of the clay minerals) and interstratified illite / smectite (48% - 57% of the clay minerals). There were no clear differences between the specimens from each of the four formations, except that there was some evidence of expandable clays found in the LBkBC specimens below 25 m depth. The presence of illite / smectite and kaolinite is suggestive of some surficial weathering.

Organic content

There is no evidence of organic material in the DBC. Loss on ignition values are generally close to zero.

Specific gravity

The specific gravity of DBC is typically 2.70. There is no clear difference in the results from the various formations.

SOIL PLASTICITY

Values of liquid limit and plastic limit for the DPT site are plotted against depth on Figure 3 and on the “A-line” plasticity chart on Figure 5. Except for the presence of some clayey lenses in the LBrBC, the values are remarkably uniform and data for all four materials fall in the classification “clay of low plasticity” on the plasticity chart. Natural moisture content values fall very close to the plastic limit. Detailed assessment of the data in Table 2 confirms that the average values of index properties for all four materials are very similar. In the field the LBkBC clay appeared to be the most plastic unit. This is in conflict with the limited laboratory data (4 results), where it appears to have a slightly higher average plastic limit with a correspondingly lower average plasticity index than the other units. Again data from the DPT site are very similar to those reported by others, see Table 2.

IN SITU STRESS

As many of the more recent developments in Dublin involve two to three levels of basement car parking, engineers regularly face the problem of attempting to estimate the degree of overconsolidation and the coefficient of earth pressure at rest (K_0). It is not possible to estimate these parameters directly from the geological history of the Dublin sites. This is because the depositional environment of these lodgement tills was complex

and there is a high degree of uncertainty regarding the stress conditions and pore water pressures imposed by past glaciations. Certainly it was unlike that of marine or lakebed deposits, which were sedimented, consolidated and possibly also unloaded under one-dimensional conditions.

For tills it seems likely that the one of the most important mechanisms resulting in the heavily loaded state of the material is shearing during glacial advance rather than compression under the weight of glacier ice. This has been confirmed by Garneau et al. (2004) who carried out tests on a Dutch glacial till in a lateral stress oedometer and confirmed that material to have anisotropic horizontal stresses. The higher stress corresponded to direction of ice advance.

In the absence of data, to date engineers in Dublin have based their estimate of K_0 from published measurements by others, as summarised on Table 3. Values of K_0 in the range 1.0 to 1.5 have been assumed in design.

For the DPT and Ballymun projects a variety of techniques were used to estimate K_0 as summarised on Table 4. For a variety of reasons all of the tests proved problematic. High pressure dilatometer tests values show considerable scatter and range between 0.2 and 2.5 with an average of about 1.5 and show a tendency for a decrease with depth as would be expected. Powell and Butcher (2003) point out that estimates of in situ stress from pressuremeter tests in tills are difficult due particularly to the stony nature of the material. As cores had to be cut using a heavy-duty rotary saw, it is likely that any residual suction close to the ends was removed during his cutting process, thus giving low values. In the special triaxial tests the samples were loaded axially at slow rates and the horizontal stress was increased in order to maintain horizontal strain close to zero. Horizontal strain

was measured by a local (Hall effect) gauge. Three series of tests were carried out with relatively low values being recorded in each case. In these tests it is not clear whether a measurement is being made of the stress condition required to maintain zero lateral strain on a disturbed sample or the in situ K_0 value.

Current practice in Dublin (e.g. Dougan et al. 1996, Long, 1997) is to use K_0 values for DBC in the range 1.0 to 1.5. In the absence of further data from in situ testing (e.g. hydraulic fracture) and lab testing (e.g. lateral stress oedometer) it is recommended that designers continue to use these values and assess the sensitivity of the output to the assumptions.

PERMEABILITY

In the absence of permeable zones, in-situ mass permeability (k) of the DBC is a key factor in controlling the behaviour in excavations. For the DPT site use was made of the natural ability of the DBC to stand unsupported at steep slopes (Long et al., 2003 and Menkiti et al, 2004). It was therefore very important to characterise the permeability of the intact cohesive clay till and the more permeable zones. A variety of techniques were used to determine k as summarised on Table 5.

It can be concluded from the measurements that typical permeability values for the intact cohesive till in the UBkBC and UBrBC formations are in the range 10^{-9} m/s to 10^{-11} m/s. For design and finite element analyses at the DPT site, a moderately conservative value for the mass permeability of cohesive till of 10^{-9} m/s was used (Menkiti et al, 2004). A higher value of 10^{-8} m/s was adopted for the UBrBC. The mass permeability for hydraulically continuous silty / granular zones can be taken as 10^{-6} m/s. A similar range of 10^{-11} m/s to 10^{-8} m/s for the UBkBC was suggested by Lehane and Simpson (2000).

Anisotropy of permeability

Permeability values as summarized above are thought to be appropriate values for horizontal flow in the till. Comparison of in situ and lab data (Table 5) suggests some degree of anisotropy with perhaps vertical permeability likely to be an order of magnitude lower. This is consistent with the fabric and geology of the DBC units (Skipper et al, 2005).

SAMPLE QUALITY

Three methods have been used to assess sample quality, see Figure 6a and Table 6. Initial effective stress (or suction) in the samples, u_r , is compared with Ladd and Lambe's (1963) "perfect sampling" stress (σ_{ps}') (K_0 assumed = 1.5 for DPT. If $K_0 = 1$, $\sigma_{ps}' = \sigma_{v0}'$, where σ_{v0}' is the in-situ vertical effective stress). Suction was measured in a triaxial cell by applying an initial cell pressure to the samples under undrained conditions, and recording the equilibrium pore pressure. Also plotted are; (i) the normalised volume change ($\Delta V/V_o$), and (ii) the normalised void ratio change ($\Delta e/e_o$) – both measured during consolidation to the best estimate of in-situ stress following the work of Lunne et al. (1997) and others. For the DPT site, it appears that the residual effective stresses (u_r) are low and only come close to the σ_{v0}' or σ_{ps}' values near the top of the sequence. However, these low values could be due to the testing technique used, as filter paper was attached to the samples to accelerate consolidation.

For the DPT block samples $\Delta V/V_o$ and $\Delta e/e_o$ values are low and the specimens can be categorised as "very good to excellent". The 1996 and 2002/2003 cores are also generally of high quality, with more scatter in the data for the 1996 cores. These 1996 cores were recovered with a mixture of conventional double and triple tube core barrels. The quality

of the 2000 cores is generally poorer than the other two sets. This increase in quality of the GeoBore-S cores with time possibly reflects improved experience in operating this technique in DBC, reorientation of the core head face discharge to minimise disturbance and also a switch from air mist to polymer gel as a flushing medium.

Initial sample suctions for Ballymun (Figure 6b) are relatively high and close to σ_{ps}' . Suction values also increase with depth and the trend is for little deviation from the “perfect” sampling line, indicating that sample quality is consistently high. Measured values are generally higher than for the DPT site. This is likely to be due to the absence of filter drains on the specimens in this case. Average $\Delta V/V_0$ and $\Delta e/e_0$ values are also low (Table 6).

From the point of view of the practising engineer these results confirm that triple tube coring techniques and block sampling both provide high quality samples from which the results of the strength and stiffness tests are more representative of the in situ conditions.

ONE DIMENSIONAL COMPRESSION BEHAVIOUR

Typical maintained load oedometer tests and triaxial isotropic compression tests for UBkBC from the Dáil Eireann site are shown on Figure 7 (Brangan, 2006). Based on the rounded nature of the conventional log stress (σ_v') against void ratio (e) plots and following the discussion on the mode of formation of the material above there is no clear evidence of a “preconsolidation” stress (p_c'). It is probable that the concept of a p_c' , as applied to normal sedimented clay, is not relevant for this material. Any numerical value for p_c' that may be obtained could simply be an artefact of the way the data are plotted.

Inspection of the σ_v' versus constrained modulus M plot ($M = 1/m_v$) shows a gradual increase in M with applied stress and suggests the material behaves much more like sand or a silt than clay (Janbu, 1985), see Figure 7. For sand or silt Janbu (1985) suggested:

$$M = m(\sigma' \sigma_a)^{0.5}$$

where $\sigma_a = 100$ kPa. These plots imply that the material has a modulus number (m) of about 250, which is typical for a natural sand or silts with water content of about 10%.

Compressibility and expansibility

With due regard to the comments made above on the applicability of conventional 1D consolidation theory to DBC, the curves presented on Figure 7 suggest that the material has compression index (C_c) in the range 0.05 to 0.08. These are equivalent to critical state λ values of between 0.022 to 0.034, which are more or less identical to those, suggested by Lehane and Faulkner (1998) for DBC. Similarly the swelling index (C_s) lies in the range 0.004 to 0.007 (equivalent to κ in the range 0.002 to 0.003) again very similar to values suggested by others for DBC.

Coefficient of consolidation

Due to the small (76 mm to 100 mm in diameter and 19 mm high) specimen size generally used in the tests a wide variety of results for the coefficient of consolidation (c_v) has been reported. Hanrahan (1977), Lehane and Simpson (2000) and Brangan (2006) suggest values may fall in the range 40 ± 20 m²/year. Similar large uncertainty in the assessment of field c_v of glacial tills has been reported by others (e.g. Trenter, 1999). Consequently, it is recommended that calculations be performed using M and k as an alternative to c_v .

SMALL STRAIN STIFFNESS

In order to provide input for finite element analyses of the retaining walls and deep shafts at the DPT site, significant efforts were made to determine the small strain shear stiffness of the various units and its variation with strain. Techniques used at the DPT site included:

- cross-hole seismic,
- seismic refraction,
- multi-channel analysis of surface waves (MASW),
- shear wave velocity measurements using bender elements on triaxial specimens,
- measurements from Hall effect gauges mounted on triaxial samples,
- values measured using unload / reload loops in the high-pressure dilatometer tests.

In addition at St. James Hospital site both cross-hole seismic and MASW surveys were carried out. At Ballymun, Dáil Eireann, and Mater Hospital triaxial tests were conducted using sample-mounted transducers.

In-situ measurements of small strain shear modulus ($G_{\max}$) at the DPT site are plotted against depth on Figure 8 together with the stratigraphy at the test location. It can be observed that $G_{\max}$ increases rapidly with depth from about 250 MPa in the UBrBC to about 1000 MPa at a depth of 8m (in the UBkBC) and more slowly below this level. However, it increases sharply to about 2000 MPa in a dense sand layer at Shaft WA2, which is reflected in the cross-hole seismic data. Slightly higher values of 1000 MPa to 1500 MPa are measured in the LBkBC, reflecting the high boulder content observed in this unit during excavation of Shaft WA2.

A summary of results of laboratory bender element tests are also superimposed on Figure 8 and the data seem to lie towards the lower bound of the in-situ data. This is likely to be due to sample disturbance effects in the 1996 rotary cores. It may also be due, in part, to specimen preparation difficulties associated with inserting the benders into the very stiff and stony samples. It was first necessary to excavate a small hole in the specimen and then seal the bender element in this hole using a mixture of epoxy resin and reworked till. In general there is very good agreement between the results from the three in situ geophysical techniques. Clearly the resolution of the seismic refraction data is poorer than that from either the MASW or cross-hole tests.

Further evidence of the reliability and accuracy of the MASW technique is provided by Donohue et al. (2003) for work at the St. James Hospital site, as shown on Figure 9a. Agreement between the two in situ techniques is excellent. The practical implication of this work is that the relatively inexpensive MASW technique can be reliably used for determining in situ shear wave velocity (and hence $G_{\max}$) in DBC.

Shear wave velocity (V_s) measurements for various DBC sites obtained using the MASW technique are shown on Figure 9b (Donohue et al., 2003, Donohue, 2005). It can be seen that, except perhaps for the St. James hospital site, the values are very similar suggesting the material is relatively uniform across the city.

STRESS – STRAIN BEHAVIOUR

Triaxial deviator stress – strain and stress paths

Following measurement of u_r as described previously, specimens were saturated then consolidated in two stages, first isotropically to $0.5\sigma_{v0}'$, and subsequently anisotropically to $(\sigma_{v0}', \sigma_{h0}')$, where σ_{h0}' is the in-situ horizontal effective stress, based on the assumed K_0

value. This final stress state was maintained until the samples stabilised (i.e. rate of volume change $< 0.001\%$ / per minute). Thereafter, the samples were sheared in undrained compression (CAUC) or extension (CAUE) at a strain rate of 4.5% per day. Some drained tests were also undertaken.

Plots showing some typical stress / strain behaviour and stress paths [in $(\sigma_a' + \sigma_r')/2$, $(\sigma_a' - \sigma_r')/2$ space) for the UBrBC, UBkBC and LBrBC are shown on Figure 10 and the following conclusions / comments can be made:

- in general the behaviour of all three materials is similar, with the UBrBC being weaker than the other two (see also Figure 13),
- the materials exhibit a strong dilatant behaviour,
- the materials possess a strong anisotropy of undrained shear strength with s_u in compression being three to four times that in extension,
- there is not strong evidence for anisotropy of effective strength parameters,
- there is some evidence that the quality of the block samples is marginally better than that of the rotary core (2002/2003) samples.

Pore pressure response

Pore pressure response for typical compression tests is shown on Figure 11. The behaviour of the UBkBC and the LBrBC is similar. Initially positive pore pressure changes are generated up to strain of about 1.5% followed by strong dilatant behaviour, with net negative pore pressures being developed after about 3.5% strain. The response of the UBrBC follows a similar pattern but is much more muted.

The strong dilatant behaviour of the UBkBC and the LBrBC has significant implications for the observational approach as used in the construction of steep cuts in the material,

such as on the DPT site. Such ductile behaviour will mean that, with careful monitoring, a warning of an impending failure will be apparent some time before the event.

Variation in stiffness with strain

Plots of undrained secant Young's modulus (E_u) against strain, for the same triaxial tests as for Figure 10, are shown on Figure 12. From the plots it can be observed that:

- all three material exhibit strong non-linearity of stiffness,
- stiffness increases with depth,
- stiffness in triaxial compression and extension are more or less the same,
- there is no significant difference between the stiffness of block samples and the 2002 / 2003 rotary cored samples,
- the projected small strain stiffness from triaxial test results is similar to those derived from the in situ MASW testing.

From the point of view of practising engineers, the implication of this latter point is that a combination of good quality triaxial tests on rotary cored samples and the relatively inexpensive in situ MASW technique can be used to estimate the full stiffness – strain relationship.

At present in Ireland, practising engineers usually adopt a simple linear elastic – perfectly plastic constitutive model. A single “operational” value of $E_u = 100$ MPa is used as derived from field observations by Farrell et al. (1995b). From the DPT tests, presented on Figure 12, this value coincides with axial strains of the order of 0.01% to 0.1%, which seems reasonable for the normal level of strain encountered in engineering works.

Stiffness values from unload – reload loops in the high-pressure dilatometer tests are also shown as insets on Figure 12. Shear modulus from the dilatometer tests have been

converted to undrained modulus of elasticity and cavity strain has been converted to shear strain after Jardine (1992). These stiffness values correspond to shear strains of the order of 0.05% to 0.7% and can be seen to be significantly higher than the equivalent values from the triaxial tests. This possibly suggests some degree of stiffness anisotropy, consistent with the geological origin of the material, with horizontal values being perhaps four times greater than vertical ones. It may also reflect the presence of cobbles at the test pocket. The implied level of stiffness anisotropy is inconsistent with the triaxial data, for which the major principal stress is vertical (compression) or horizontal (extension), although the triaxial data also includes changes to the relative magnitude of the intermediate principal stress. Further work is required on stiffness anisotropy of the DBC as insufficient data is available to make definitive conclusions.

Comparison with other well characterised materials

Figures 9b and 12 show a comparison between typical in situ shear wave velocity and normalised stiffness values (E_u/p') for UBkBC and LBrBC and data for London clay (Hight et al., 2003) and Cowden till from the east coast of the UK (Powell and Butcher, 2003) respectively. Dublin boulder clay stiffness values are extremely high when compared to other stiff clays. It is about six to eight times stiffer than London clay and about five times stiffer than Cowden till.

Stiffness from FE back-analysis

For finite element analyses of various works on the DPT site, the DBC was assumed to have isotropic stiffness properties. The stiffness model for UBkBC and LBrBC used in the original finite element models is shown on Figure 12. It can be seen that it was based mainly on the results of triaxial testing and laboratory Bender element testing. As has

been discussed previously it is now recognised that the effects of sampling disturbance and perhaps stiffness anisotropy mean that these original values were conservative. Subsequent back-analyses of an unsupported cut trial excavation (Menkiti et al., 2004) and the lateral movements of the diaphragm walls supporting shaft WA2 (Cabarkapa et al., 2003) have confirmed this to be the case. A revised stiffness model required to fit the measured movements is shown on Figure 12.

UNDRAINED SHEAR STRENGTH

CAUC / CIUC / CAUE triaxial testing

The undrained shear strengths (s_u) measured in the CAUC, CIUC or CAUE tests are presented on Figure 13 and Table 7, where these tests are defined. Although the choice of s_u for a dilatant / strain hardening material is not straightforward, peak values have been used here to be consistent with current Irish practice. Values normalised by the initial mean effective stress, p'_0 are also given and average values are presented on Table 7. Other researchers have taken s_u at a limiting strain (e.g. 2%), at the point where the stress path comes close to the Mohr-Coulomb failure line or when pore pressure become negative. In this case the first two techniques would give significantly lower s_u values, whereas the latter approach would result in similar values to those obtained from the simple peak. For engineering works, control of deformation may be the dominant design factor and design stress must be consistent with tolerable strain.

Despite some scatter in the data, there is a trend for increasing strength with depth in the UBrBC and UBkBC from a value of about 80 kPa in the UBrBC to about 500 kPa at the boundary of the UBkBC and LBrBC clays at about 10 m depth. A similar trend can be seen in the normalised data and the values of s_u/p'_0 are indicative of material previously

subjected to high load. The trend in s_u/p_0' , particularly that for the CIUC tests, is similar to the relationship suggested by Lehane and Simpson (2000), see Figure 13. Lehane and Simpson's data were from CIUC tests on 100 mm diameter rotary cored samples, similar to the 1996 cores under study in this paper. Lehane and Faulkner (1998) report s_u/p_0' values of about 0.45 for normally consolidated reconstituted DBC. This value represents the lower bound for the data presented on Figure 13.

It is not thought that these high values are strongly influenced by the stone content. This was not so high as to mean the pieces were touching. They were generally surrounded by a matrix of “clayey” material. These high strength values are consistent with field observations. Significant mechanical effort is required to excavate the material and the perceived strength and stiffness increase with depth.

Extension strength (CAUE) data are also shown in Figure 13 and Table 7 (K_0 was assumed = 1.5). These tests give surprisingly low values, which increase approximately linearly from about 20 kPa near the surface to 130 kPa at 12 m depth. This linear increase with depth is not as apparent for the normalised data. Strength anisotropy ratio s_{u-CAUE} / s_{u-CAUC} is about 0.25. Other researchers (e.g. Karlsrud et al, 2005) suggest that this ratio should be of the order of 0.4 to 0.5 for material with an I_p of 10% to 15%. It was observed that most of the samples failed by forming shallow dipping failure planes (necks), which often engaged pre-existing discontinuities. It seems likely that the low values are due to the granular nature of the material. In contrast compression failure was consistently of the classical “barrel” type.

Further study is warranted to investigate the implied anisotropy of undrained shear strength and the practical implications for engineering works.

UU triaxial testing

Unconsolidated undrained (UU) triaxial tests are frequently used in practice given the time and cost constraints of carrying out more sophisticated tests. These tests are used as classification tests as well as tests to produce design parameters, so a good number of tests are usually carried out. Results from a series of UU tests on the DPT 2002/2003 rotary cored specimens from a single borehole are presented on Figure 14a and summarised on Table 8. For all the units s_u values from UU and CIUC tests are very similar. Average CIUC s_u value for the UBkBC and LBrBC are 287 kPa and 298 kPa respectively compared to 217 kPa and 383 kPa from the UU tests. A similar finding was made at the Ballymun site (Figure 14b and Table 9). Sample quality assessment for these tests was presented on Figure 6b. Data from two laboratories, UCD and a commercial laboratory, are reported. This result has practical implications in that, once high quality rotary core samples are available, it may be adequate to carry out cheaper UU rather than more expensive and time consuming CIUC tests.

In situ testing

Standard penetration test “N” values for the DPT site are also shown on Figure 13 (all data with equivalent “N” > 100 has been omitted due to probable influence of cobbles). Although, like UU tests the problems with SPT testing have been thoroughly discussed in the literature, the test is performed routinely in ground investigations in Ireland. The observed scatter in the data is considerable and typical, reflecting the large and variable stone content of the till. Stroud and Butler (1975) and Stroud (1989) suggests that for a glacial till with average plasticity index of about 12%, the ratio $f_1 = s_u / N_{avg}$ is about 6.0. Farrell and Wall (1990) report a similar value for the UBrBC and UBkBC again based on

CIUC or UU triaxial tests. Data for the DPT and Ballymun sites are summarized on Figures 13 and 14 and Tables 8 and 9 and suggest $f_1 = 6$ may be appropriate for UU and CIUC tests but that a higher value of f_1 could apply to CAUC tests.

Some in situ s_u data are also available from high pressure dilatometer tests at the DPT site. Data were interpreted according to the limit pressure approach advocated by Powell and Butcher (2003) for Cowden till ($s_u = \text{limit pressure} / 6.18$). This analysis resulted in very high values of s_u , being on average about 835 kPa for the UBkBC and LBrBC. These authors show that this approach gives results consistent with large diameter plate tests. Other available interpretation techniques (see review by Mair and Wood, 1985) often give much higher values of s_u . This is likely to be due to fact that most of these techniques were developed for either stone free contractant sedimentary clays or weak rocks, rather than the highly dilatant material under consideration here. It is also possible that in the DBC the tests were at least partially drained hence resulting in the higher strength values.

Undrained strength values in till reported by others

Undrained shear strength values reported for other tills are summarised on Table 10. s_u values for the Dublin till are often considerably higher. The reasons for this are not clear but DBC seems to have higher stone content than that encountered elsewhere.

EFFECTIVE STRESS SHEAR STRENGTH

Intact till

From the stress path plots presented on Figure 10, it appears:

1. The materials have a peak effective friction angle (ϕ'), in compression, of about 44° .
This somewhat high value may be consistent with the nature of the clay fraction and the relatively high sand content in the till.
2. Large deformation strength corresponds to ϕ' of about 36° . This similar to the critical state friction angle (ϕ_{cv}') of $34 \pm 1^\circ$ suggested by Lehane and Faulkner (1998).
3. This divergence of the stress paths from the linear Mohr-Coulomb envelope at high strains may be indicative of the development of failure along some fissures or joints within the specimen rather than a mass failure of the material, similar to that reported by Vaughan and Walbancke (1975) for Cow Green till.
4. In triaxial extension ϕ' appears to be about 36° , i.e. similar to the critical state or large strain compression value. This again may be due to failure along some microstructural feature in the material.
5. Effective cohesion (c') is close to zero. This is consistent with the small and often rotund clay-sized fraction, the mode of formation, involving a high degree of shearing and lack of evidence of cementation bonding between the particles in fabric studies.

Peak friction angles (assuming $c' = 0$) have been plotted against the mean consolidation stress (p_0') on Figure 15. There is a clear tendency for decreasing friction angle with increasing effective stress, particularly for the extension tests. Thus the material has a curved rather than linear failure surface, similar to the conclusions of Atkinson and Little (1988) for St. Albans till and Robertson et al. (1994) for Northumberland till.

Reconstituted till

Lehane and Faulkner (1998) report results of triaxial tests on reconstituted DBC. All drained and undrained stress paths terminate on a straight lines passing through the

origin, when p' at failure exceeds 200 kPa. These lines corresponds with $\phi' = 34 \pm 1^\circ$ in both compression and extension. This value is identical to ϕ_{cv}' and confirms that the behaviour of intact DBC in shear compares well with the behaviour of reconstituted material. Gens and Hight (1979) and others have found a similar result.

Large strain (residual) strength

Loughman (1979) studied the residual shear strength of DBC and found that in general the ϕ_{res}' was high ($>30^\circ$) due to the high silt content of the material. This confirms that, as would be expected from the mode of formation of the material, it has low sensitivity.

CONCLUSIONS

There are significant economic benefits in understanding the characteristics of Dublin Boulder Clay (DBC) as it underlies much of the city. This paper gives geotechnical characteristics of the various formations comprising the DBC and some of the main findings, which may be of concern to practising engineers, are as follows:

- There are clear differences in the engineering parameters between the four units of DBC as defined by Skipper et al. (2005).
- The two uppermost units are the most important from the point of view of engineering projects and these seem to be relatively homogenous with depth and with location throughout the city.
- Localised granular lenses can be encountered. These can have very significant practical implications for example for pile construction and temporary slope stability.
- High quality samples of DBC can be obtained using triple tube rotary techniques with polymer flush or block sampling where access permits.

- For such high quality samples, triaxial CIUC or CAUC tests on these high quality cores give similar s_u values to simple UU tests.
- DBC possesses a high degree of anisotropy of undrained shear strength.
- DBC is considerably stiffer and stronger than other tills documented in the literature.
- Inexpensive MASW surface wave studies can give reliable in situ shear wave velocity (and thus small strain stiffness) values. These data combined with that from triaxial tests, which include sample-mounted transducers, can give the full stiffness – strain response of the material for design purposes.
- DBC appears to have a curved effective stress failure envelope with negligible effective cohesion.
- Comparison of field (horizontal) permeability values and lab (vertical) values suggest some degree of permeability anisotropy, with horizontal permeability being greater than the vertical permeability.
- the material may exhibit some degree of anisotropy of permeability.

Due to the complicated depositional process involved in situ horizontal stress in DBC is poorly understood. Similarly anisotropy of stiffness has not been fully explored. Both of these parameters have important implications for future work in Dublin, which will involve deep excavations (e.g. the central Dublin section of the Metro project). Work should be carried out in the lab using recently developed techniques such as lateral stress oedometers and bender elements testing with multiple shear wave directions. Future field investigations should include hydraulic fracture testing and various complementary geophysical techniques.

ACKNOWLEDGMENTS

The authors are particularly grateful to George Cosgrave, Senior Laboratory Technician at UCD, who carried out much of the laboratory testing and to Shane Donohue of UCD for the MASW survey results. Colleagues at GCG, particularly David Hight and George Milligan have provided useful insights into the behaviour of DBC and other stiff clays. The authors would like to thank NMI Joint Venture and Dublin City Council for permission to publish the DPT data.

NOTATION

AR	Sampler area ratio = $(A_e - A_c) / A_c$, where A_e and A_c are the external and internal areas of the cutting shoe
C_c	compression index
C_s	swelling index
G_{max}	small strain shear modulus
N	standard penetration test value
c'	effective cohesion
c_v	coefficient of consolidation
e	void ratio
f_1	s_u / N_{avg}
k	coefficient of permeability (h and v correspond to horizontal and vertical)
m	modulus number, i.e. slope of normally consolidated part of M versus σ'_v curve
m_v	coefficient of unit volume change
p'	mean effective stress = $(\sigma'_a + 2\sigma'_r)/3$
p_0'	in situ mean effective stress = $(\sigma_{v0}' + 2\sigma_{h0}')/3$

p_c'	preconsolidation stress
u_r	initial sample suction (or residual effective stress)
s'	mean effective stress = $(\sigma_a' + \sigma_r')/2$
t'	shear stress = $(\sigma_a' - \sigma_r')/2$
s_u	undrained shear strength
E_u	undrained secant Young's modulus
K_0	co-efficient of earth pressure at rest = $\sigma_{h0}' / \sigma_{v0}'$
M	constrained modulus
$\Delta V/V_0$	normalised volume change during consolidation
$\Delta e/e_0$	normalised void ratio change during consolidation
ϕ'	effective friction angle
ϕ_{cv}'	critical state friction angle
ϕ_{res}'	residual (high strain) friction angle
κ	slope of swelling line
λ	slope of isotropic compression line
σ_a'	axial effective stress
σ_r'	radial effective stress
σ_{h0}'	in situ horizontal effective stress
σ_{v0}'	in situ vertical effective stress

REFERENCES

- Al-Shaikh-Ali, M.M.H, Davis, A.G. and Lloyd, M.J. (1981). In situ measurement of K_0 in a stiff fissured glacial till by hydraulic fracturing. Ground Engineering, 14, No. 1, 19 - 25.

- Atkinson, J.H. and Little, J.A. (1988). Undrained triaxial strength and stress-strain characteristics of a glacial till soil. *Can. Geo. Jnl.*, 25, No. 3, 428 – 439.
- Boylan, N. and Carolan, A. (2004). The influence of permeability on the stability of steep slopes in glacial till. Unpublished final year project, Department of Civil Engineering, University College Dublin.
- Brangan, C. (2006). Behaviour of deep excavation in Dublin glacial till. Unpublished PhD thesis, Department of Civil Engineering, University College Dublin, March.
- BS 1377: 1990. British Standard methods of tests for soils for civil engineering purposes.
- BS 5930: 1999. British Standard code of practice for site investigations.
- Cabarkapa, Z., Milligan, G.W.E, Menkiti, C.O., Murphy J. and Potts D. M. (2003). Design and performance of a large diameter shaft in Dublin Boulder Clay. *British Geotechnical Association International Conference on Foundations, Dundee, Thomas Telford*, 175 – 185.
- Chandler, R. J. and Gutierrez, C.I. (1986). The filter-paper method of suction measurement. *Geotechnique* 36, 2, 265-268.
- Chegini, A. and Trenter, N.A. (1996). The shear strength and deformation behaviour of a glacial till. *Advances in Site Investigation Practice, Thomas Telford, London*, 851 – 866.
- Dobie, M.J.D. (1989). The use of cone penetration tests in glacial till. *Penetration testing in the UK. Thomas Telford, London*, 93 – 96.
- Donohue, S., Gavin, K, Long, M. and O'Connor, P. (2003). G_{max} from multichannel analysis of surface waves for Dublin boulder clay. *Proc. 13th. ECSMGE, Prague, Swets and Zeitlinger*, 2, 515 - 520.

- Donohue, S. (2005). Assessment of sample disturbance in soft clay using shear wave velocity and suction measurements. Unpublished PhD thesis, Department of Civil Engineering, University College Dublin, October 346p.
- Dougan, I, Long MM and Byrne JJB (1996). The Geotechnical Aspects of the Deep Basement for the Jervis St. Shopping Centre. Trans. Institution of Engineers of Ireland, Vol. 120, 49 - 70.
- Farrell, E. R. and Wall, D. (1990). The soils of Dublin. Transactions of the Institution of Engineers of Ireland, Vol. 115, 78 - 97.
- Farrell, E.R., Coxon, P., Doff, D. and Fried'homme, L. (1995a). Genesis of brown boulder clay in Dublin. Quarterly Journal of Engineering Geology, 28, 143 – 152.
- Farrell, E., Lehane, B., O'Brien, S. and Orr, T. (1995b). Stiffness of Dublin black boulder clay. Proc. XIth ECSMFE, Copenhagen, 1, 1-109 – 1-117.
- Garneau, L.F., Molenkamp, F, Sharma, J. and Hegtermans, B.M.H. (2004) Engineering geology of glaciated soils. Skempton Memorial Conference, Advances in Geotechnical Engineering, Eds. Jardine et al., March, Thomas Telford, 2, 1280 – 1291.
- Gens, A. and Hight, D.W. (1979). The laboratory measurement of design parameters for a glacial till. Proc. 7th ECSMFE, Brighton, UK, 2, 57 – 65.
- Handy, R.L., Remmes, B., Moldt, S., Lutenegeger, A.J. and Trott, G. (1982). In situ stress determination by Iowa stepped blade. ASCE Journal of the Geotechnical Engineering Division, 108, GT11, 1405 – 1422.
- Hanrahan, E.T. (1977). Irish glacial till: origin and characteristics. An Foras Forbartha, Dublin. BC 164.

- Hawkins, P.G., Mair, R.J., Mathieson, W.G. and Muir Wood, D. (1990) Pressuremeter measurement of total horizontal stress in stiff clay. Proc. 3rd Int. Symp. Pressuremeters, Thomas Telford. London.
- Hight, D.W., McMillan, F., Powell, J.J.M., Jardine, R.J. and Allenou, C.P. (2003). Some characteristics of London Clay. Characterisation and Engineering Properties of Natural Soils, Tan et al. eds. Balkema, 2, 851 - 908.
- Janbu, M. (1985). Soil models in offshore engineering. 25th Rankine Lecture, Geotechnique, 35, No. 3, 241 – 281.
- Jardine, R.J. (1992). Nonlinear stiffness parameters from undrained pressuremeter tests. Canadian Geotechnical Journal, 29, 436 – 447.
- Karlsrud, K., Lunne, T., Kort, D.A. and Strandvik, S. (2005). CPTU correlation for clays. Proc. 16th ICSMGE, Osaka, September.
- Kleven, A., Lacasse, S. and Andersen, K.H. (1986). Foundation engineering criteria for gravity platforms. Soil parameters for offshore foundation design. Part II, NGI Report 40013-34, April.
- Ladd, C.C. & Lambe, T.W. (1963). The strength of “undisturbed” clay determined from undrained tests. ASTM Special Tech. Pub. No. 361, Symposium on Laboratory Shear Testing of Soils, 342 – 371.
- Lehane, B. and Faulkner, A. (1998) Stiffness and strength characteristics of a hard lodgement till, The Geotechnics of Hard Soils-Soft Rocks, Evangelista & Picarelli (eds.), Balkema, Rotterdam.
- Lehane, B. and Simpson, B. (2000). Modelling glacial till under triaxial conditions using a BRICK soil model. Can Geo. Jnl., 37, 1078 – 1088.

- Long, MM (1997). Design and Construction of Deep Basements in Dublin, Ireland. Proc XIV Int. Conf. on Soil Mech. and Foundation Engineering, Hamburg, Germany , September 1997, Vol. 2, 1377-1380.
- Long, M., Menkiti, C.O., Kovacevic, N., Milligan, G.W.E., Coulet, D. and Potts, D.M. (2003). An observational approach to the design of steep sided excavations in Dublin glacial till. Proc. Underground Construction 2003, UC2003, London, Sept., Hemming-Group Ltd., 443 – 454.
- Long, M., Menkiti, C.O. and Follet, B. (2004). Some experience in measuring pore water suctions in Dublin glacial till. Geotechnical News / Geotechnical Instrumentation News, 22, No. 3, 21 – 27.
- Loughman, G. (1979). The residual shear strength of Irish glacial till. Unpublished MSc Thesis, University of Dublin, Trinity College.
- Lunne, T., Berre, T. and Strandvik, S. (1997). Sample disturbance effects in soft low plasticity Norwegian clay, Proc. Conf. on Recent Developments in Soil and Pavement Mechanics, Rio de Janeiro, Balkema, 81-102
- Lutenegger, A.J. (1990). Determination of in situ lateral stresses in a dense glacial till. Transportation Research Record, 1278, 194 – 203.
- Mair, R.J. and Wood, D.M. (1985). Pressuremeter testing: Methods and interpretation. CIRIA and Butterworth.
- Marsland, A and Randolph, M.F. (1977). Comparisons of results from pressuremeter tests and large in-situ plate tests in London clay. Geotechnique, 27, No. 2, 217 – 243.
- McKinlay, D.G., Tomlinson, M.J. and Anderson, W.F. (1974). Observations on the undrained strength of glacial till. Geotechnique, 24, No. 4, 503 – 516.

- Menkiti, C.O., Long, M., Kovacevic, N., Edmonds, H.E., Milligan, G.W.E. and Potts, D.M. (2004). Trial excavation for cut and cover tunnel construction in glacial till - a case study from Dublin. Proc. Skempton Memorial Conference, Advances in Geotechnical Engineering, Eds. Jardine et al., March, Thomas Telford, 2, 1090 – 1104.
- Milligan, G.W.E., Menkiti, C.O., Long, M., Kovacevic, N., Paterson, S.R., Coulet, D. and Potts, D.M. (2006). Design and performance of fully and partly nailed slopes in Dublin boulder clay. Submitted for publication in Geotechnique, March 2006.
- Orr, T. L. L. and Farrell, E. R. (1996). Geotechnical aspects of tunnelling in soft ground in Ireland. Geotechnical Aspects of Underground Construction in Soft Ground, Mair & Taylor (eds.), Balkema, Rotterdam.
- Powell, J.J.M. and Butcher, A.P. (2003). Characterisation of a glacial clay till at Cowden, Humberside. Characterisation and Engineering Properties of Natural Soils, Tan et al. eds. Balkema, 2, 983 - 1020.
- Robertson, T., Clarke, B.G. and Hughes, D.B. (1994). Classification and strength of Northumberland Till. Ground Engineering, 27, No. 10, 29 – 34.
- Skipper, J., Follet, B., Menkiti, C.O, Long, M, Clarke – Hughes, J. (2005). The engineering geology and characterisation of Dublin Boulder Clay. Quarterly Journal of Engineering Geology and Hydrogeology (QJEGH), 38, 171 - 187.
- Stroud, M.A. and Butler F.G. (1975). The standard penetration test and the engineering properties of glacial material. Proc. Sym. On The Engineering Behaviour of Glacial Materials, University of Birmingham, April, Published by The Midlands Geotechnical Society, 1249 – 135.

Stroud, M.A. (1989). The standard penetration test: its application and interpretation.

Penetration testing in the UK, Thomas Telford, London, 29 – 49.

Trenter, N. A. (1999). Engineering in glacial tills. CIRIA Report C504.

Vaughan, P.R. and Walbancke, H.J. (1975). The stability of cut and fill slopes in boulder clay. Proc. Sym. On The Engineering Behaviour of Glacial Materials, University of Birmingham, April, Published by The Midlands Geotechnical Society, 209 – 219.

Table 1. Summary of sites considered other than Dublin Port Tunnel

Site	Project	Field work	Lab data	Reference
Ballymun Northern Gateway.	Raft foundation for a large tower block,	High quality Geobore-S cores	u_r , K_0 , stiffness from local strain gauge transducers. s_u various tests.	Brangan (2006)
Dáil Eireann	Retaining structures for a deep excavation adjacent to the Irish Parliament buildings.	High quality Geobore-S cores. Data from performance of the retaining walls	Isotropic compression, oedometer, s_u	

Mater Hospital	Large hospital structure	High quality Geobore-S cores. MASW geophysics.	s _u	
St. James Hospital (LUAS)	Platform structures and underground excavation for light rail system	MASW and cross hole geophysics.		
Iveagh Gardens	Portal for Dublin Metro	MASW geophysics		
Tallaght	Commercial development with deep excavation	MASW geophysics. Performance of retaining walls.		

Table 2. Summary of average basic material properties – DPT northern cut and cover site

	UBrBC	UBkBC	LBrBC	LBkBC
Moisture content (%)	13.1	9.7 (11±3)	11.5	11.3
Bulk density (Mg/m ³)	2.228	2.337	2.283	2.284
Liquid limit (%)	29.3	28.3 (25±4)	30.0	29.5
Plastic limit (%)	15.9	15.1	14.9	17.8
Plasticity index (%)	13.4	13.2 (11±2)	15.1	11.8
Clay content (%)	11.7	14.8 (15±5)	17.8	17.5

Silt content (%)	17.0	24.7	28.3	30.5
Sand content (%)	25.0	24.7	25.7	34.0
Gravel content (%)	46.3	35.8 (30±5)	28.0	35.5

Note: The formation most commonly encountered in Dublin is the UBkBC. Values given in brackets are from general experience in Dublin as reported by Lehane and Simpson (2000).

Table 3. Summary of K_0 measurements in till from literature

Till	Technique	K_0	Reference
Iowa, US	Stepped blade dilatometer	1.3	Handy et al. (1982)
Cheshire, UK	Hydraulic fracture and packer	0.7 to 1	Al-Shaikh-Ali et al. (1981)
Iowa, US	Dilatometer, spade cell, pressuremeter	3 to 4 to 4 m depth then decreases to 1	Lutenegger (1990)
Cowden, UK	As above	As above	Powell and Butcher (2003)

Table 4. Summary of K_0 measurements on DBC

Site	Technique	K_0	Reference used
DPT	High pressure dilatometer (Cambridge Insitu device)	0.2 to 2.5 with average of 1.5	Mair & Wood (1987) Marsland & Randolph (1977) Hawkins et al. (1990)
DPT	Filter paper	Low	Chandler & Gutierrez (1986)
DPT	Special triaxial – no pre-consolidation	0.2 to 0.3	

	Triaxial – isotropic	0.5 to 0.64	
	Consolidation to σ'_{v0}		
	Triaxial – Anisotropic	0.45 to 0.53	
	consolidation with $K_0 =$		
	0.6		
Ballymun	Special triaxial – no	0.8	
	pre-consolidation		
Ballymun	Filter paper	Low	Chandler & Gutierrez (1986)

Table 5. Summary of permeability measurements on DBC for DPT site

Technique	Measured value (m/s)	Reference
Variable head through	Intact cohesive till: 10^{-9}	BS5930
conventional piezometer	Silty / granular zones: 10^{-5} to 10^{-6}	
tips (k_h)	Mixed cohesive and granular zones: 10^{-7} to 10^{-9}	
Variable head through	Range: 10^{-12} m/s to 10^{-8}	Boylan and Carolan, 2004
vibrating wire	Representative mean: 10^{-9}	
piezometer tips with fine		

bore (k_h)		
Laboratory triaxial permeability tests (k_v)	Average value: 5×10^{-11} (low scatter)	BS1377
Consolidation stage of triaxial tests (k_v/k_h)	10^{-9} to 10^{-10}	BS1377
Rowe cell (k_v)	10^{-9} to 10^{-10} : little dependence on stress	BS1377

Table 6. Sample quality assessment – DPT and Ballymun sites

Site	Samples	Avg. u_r (kPa)	Avg. $\Delta V/V_0$ (%)	Avg. $\Delta e/e_0$
DPT	1996 cores	45.0	0.93	0.042
DPT	2000 cores	n/a	2.49	0.112
DPT	2002 / 2003 cores	24.2	0.9	0.06
DPT	2002 blocks	25.4	0.41	0.019
Ballymun	2003 cores	77	0.68	0.041

Table 7. Average laboratory s_u values – DPT site

	CIUC*		CAUC*		CAUE*	
	s_u	s_u / p'_0	s_u	s_u / p'_0	s_u	s_u / p'_0
Upper brown	n/a	n/a	84	2.25	21	0.46
Upper black	287	1.93	373	3.23	87	0.87
Lower brown	297	2.11	520	2.58	129	0.75
Lower black	240	0.98	n/a	N/a	n/a	n/a

*CIUC = consolidated isotropically undrained compression test; CAUC = consolidated anisotropically undrained compression test; CAUE = consolidated anisotropically undrained extension test.

Table 8. Average SPT “N” and laboratory s_u values – DPT site

	Avg. SPT “N” (Blows / 300 mm)	Avg. CAUC s_u (kPa)	CAUC s_u / N_{avg}	Avg. CIUC s_u (kPa)	CIUC s_u / N_{avg}	Avg. UU s_u (kPa)	UU s_u / N_{avg}
Upper brown	19	84	4.4	n/a	-	n/a	-
Upper black	53	373	7.0	287	5.4	217	4.1
Lower brown	53	520	9.8	297	5.6	383	7.2
Lower black	68	n/a	-	240	3.5	n/a	-

Table 9. Average SPT “N” and laboratory s_u values – Ballymun site

	Avg. SPT “N” (Blows / 300 mm)	Avg. CAUC s_u (kPa)	CAUC s_u / N_{avg}	Avg. UU s_u (kPa)	CIUC s_u / N_{avg}
Upper brown	18	n/a	-	n/a	-
Upper black	50	240.8	4.8	340.2	6.8

Table 10. Summary of s_u measurements on till from literature

Site	s_u (kPa)	Technique	Reference
Cowden, England	90 - 150	High quality pushed samples	Powell and Butcher (2003)
Cheshire, England	As above	UU tests on U100 samples	Dobie (1989)
Cheshire, England	As above	As above	Al-Shaikh-Ali et al. (1981)
Chapelcross, Scotland	Lower than DBC	UU tests on U100 samples	Chegini and Trenter (1996)

Glasgow, Scotland	100 - 200	UU and UC tests on U100 samples. Large dia. plate tests	Mc Kinlay et al. (1974)
North East England	50 - 410	UU, CIUC tests	Robertson et al. (1994)
Iowa, USA.	100 - 150	CIUC tests on Shelby tube samples	Lutenegger (1990)

***This file contains the figures supporting the paper by Long and Menkiti on the
Geotechnical properties of Dublin boulder clay***

LIST OF FIGURES

Fig. No.	Caption	File Name*
1	Location of sites showing outcrop of DBC	Dell/papers/dpt/characterisation/Dublin geology.doc
2	Typical view of the fabric of the of the UBkBC	Dell/papers/dpt/characterization/sem.doc
3	Soil stratigraphy, groundwater and basic parameters - DPT site	Dell/papers/dpt/basicsII.grf+basics.xls
4	Particle size distribution curves – DPT site	Dell/papers/dpt/allpsd.grf+four.xls files
5	Plasticity chart – DPT site	Dell/papers/dpt/atterberg.grf+basics.xls
6a	Sample quality – DPT site	Dell/papers/dpt/samplequality.grf+xls
6b	Sample quality – Ballymun site	D(R)/Ballymun/residual.grf+.xls
7	1D oedometer and isotropic compression tests from Dáil Eireann site	Dell/Papers/DPT/1Dcomp.grf+.xls
8	Small strain stiffness – DPT site	Dell/papers/DPT/Gmax.grf
9a	In situ shear wave velocity – St. James Hospital Location 1	Dell/Papers/DPT/James1Vsandc-h.grf
9b	In situ shear wave velocity from MASW technique – various DBC sites	Dell/Papers/DPT/MASWDublinTill.grf
10	Stress - strain behaviour and paths	Dell/Papers/DPT/Upperbrn,Upperblack, Lowerbrnstressstrain.grf
11	Pore pressure response	Dell/Papers/DPT/Porepressure.grf
12	Variation in stiffness with strain	Dell/Papers/DPT/Stiffnessupperbrown, upperblack,lowerbrown,variousstiffness .grf (4 files)
13	Undrained shear strength from SPT and CAUC, CIUC and CAUE triaxial tests	Dell/Labtests/DPT/sptsu.grf+spt.xls+su.xls
14a	Undrained shear strength from UC triaxial tests	Dell/Labtests/DPT/uu.grf+.xls
14b	Undrained shear strength – Ballymun site	D(R)/Ballymun/Ballymunsu.grf+su.xls. spt.xls
15	Effective peak friction angle	D(Q)/DPT/frictionangle.grf+friction.xls

* MICROSOFT EXCEL[®] or GOLDEN SOFTWARE GRAPHER2.0[®] used unless stated

Figure 1. Site locations showing outcrop of Dublin Boulder clay

Figure 2. Typical view of the fabric of the upper black boulder clay (UBkBC),

Figure3. Soil stratigraphy, groundwater and basic parameters DPT site

Figure 4. Particle size distribution curves – DPT site

Figure 5. Plasticity chart – DPT site

Figure 6a. Sample quality – DPT site

Figure 6b. Sample quality – Ballymun site

Figure 7. 1D oedometer and isotropic compression tests from Dáil Eireann site

Figure 8. Small strain stiffness- DPT site

Figure 9. In situ shear wave velocity from MASW technique (a) St James Hospital Location 1 and (b) various DBC sites

Upper brown boulder clay

Upper black boulder clay

Lower brown boulder clay

Figure 10. Stress – strain behaviour and stress paths

Figure 11. Pore pressure response

Figure 12. Variation in stiffness with strain

Figure 13. Undrained shear strength from SPT and CAUC, CIUC and CAUE triaxial tests

Figure 14. Undrained shear strength from UU tests (a) DPT, (b) Ballymun

Figure 15. Effective peak friction angle