Research Repository UCD

Title	Experimental Testing of a Moving Force Identification Bridge Weigh-in-Motion Algorithm
Authors(s)	Rowley, C., O'Brien, Eugene J., González, Arturo, et al.
Publication date	2008-11-18
Publication information	Rowley, C., Eugene J. O'Brien, Arturo González, and et al. "Experimental Testing of a Moving Force Identification Bridge Weigh-in-Motion Algorithm" 49, no. 5 (November 18, 2008).
Publisher	Springer-Verlag
Item record/more information	http://hdl.handle.net/10197/4853
Publisher's statement	The final publication is available at www.springerlink.com
Publisher's version (DOI)	10.1007/s11340-008-9188-3

Downloaded 2023-04-07T10:52:29Z

The UCD community has made this article openly available. Please share how this access benefits you. Your story matters! (@ucd_oa)

© Some rights reserved. For more information

Experimental Testing of a Moving Force Identification Bridge Weigh-in-Motion Algorithm

C.W. Rowley, E.J. OBrien, A. Gonzalez, A.Žnidarič

Abstract

Bridge weigh-in-motion systems are based on the measurement of strain on a bridge and the use of the measurements to estimate the static weights of passing traffic loads. Traditionally, commercial systems employ a static algorithm and use the bridge influence line to infer static axle weights. This paper describes the experimental testing of an algorithm based on moving force identification theory. In this approach the bridge is dynamically modeled using the finite element method and an eigenvalue reduction technique is employed to reduce the dimension of the system. The inverse problem of finding the applied forces from measured responses is then formulated as a least squares problem with Tikhonov regularization. The optimal regularization parameter is solved using the L-curve method. Finally, the static axle loads, impact factors and truck frequencies are obtained from a complete time history of the identified moving forces.

Keywords: Bridge, Weigh-in-motion, Force identification, Regularization, Dynamic programming, Traffic loads

Moving Force Identification Bridge Weigh-in-Motion Algorithm

The traditional static bridge weigh-in-motion (B-WIM) algorithm provides static axle weights from minimizing the sum of squares of differences between measured total bridge strain and theoretical static strain [1]. Although the deviations with respect to the static response that vehicle and bridge dynamics introduce in the measured response tend to be averaged out during the minimization process, they remain a significant source of inaccuracy [2]. This paper proposes an alternative B-WIM algorithm that calculates the time history of moving forces as they cross the bridge, based on moving force identification (MFI) theory. The MFI algorithm implemented here was developed by the authors [3–5], and is an extension of the one-dimensional algorithm by Law and Fang [6] to two dimensions. The mathematics behind general inverse theory is available in the literature [7–11]. The MFI algorithm requires a finite element (FE) mathematical model that accurately represents the static and dynamic behavior of the bridge structure. The method of dynamic programming requires that the equilibrium equation of motion be converted to a discrete time integration scheme. In this case the equilibrium equation of motion is reduced to an equation in modal coordinates defined by:

$$\begin{aligned} [I]_{n_z \times n_z} \{z\}_{n_z \times 1} + 2\zeta [\Omega]_{n_z \times n_z} \{z\}_{n_z \times 1} + [\Omega]_{n_z \times n_z} \{z\}_{n_z \times 1} \\ = \Phi^T [L(t)]_{n_{\text{dof}} \times n_g} \{g(t)\}_{n_g \times 1} \end{aligned} \quad (1)$$

where $[\Phi]$ is the modal matrix of normalized eigenvectors and n_z is the number of modes to be used in the inverse analysis. $[\Omega]$ is a diagonal matrix containing the natural frequencies and ζ is the percentage damping. $[L(t)]$ is a time varying location matrix relating the n_g applied vehicle forces of the vector $g(t)$ to the degrees of freedom, n_{dof} , of the original FE model. Tikhonov regularization [12] is applied to provide a bound to the error and ‘smoother’ solutions to the ill-conditioning nature of the MFI problem [13, 14]. The final part of the solution lies in the calculation of the optimal regularization parameter; the L-curve has been chosen to obtain the optimum [15–18]. The basic idea is to plot the discrete smoothing norm of the regularized solution versus the residual norm on a log–log scale, which will always have a ‘corner’ where the optimal regularization parameter is located.

Bridge and Truck

The testing was carried out on the Vransko Bridge in Slovenia as part of the research carried out within the European 6th Framework Project ARCHES (Assessment and Rehabilitation of Central European Highway Structures). The bridge is 24.8 m between the center line of the bearings with a total span of 26 m. The bridge has no skew and is of beam and slab construction. It has five concrete longitudinal beams (Fig. 1) and two diaphragm beams in the transverse direction over the supports. The bridge was instrumented with strain transducers on the beams at mid-span to record the input for the MFI algorithm, and at quarter points for axle detection. The data acquisition was carried out using SiWIM (B-WIM system developed by ZAG and the Cestel Company [19]). The scanning frequency was 512 Hz per channel. The first natural frequencies identified from measurements were 5.11, 6.50, 9.89, 16.12 and 20.55 Hz. Bridge damping was found to be approximately 1% for the first natural frequency. A pre-weighed rigid three-axle truck with steel suspension was used during testing. The truck had static axle weights of 75.04, 102.51 and 101.04 kN. The first and second axle spacings were 3.56 and 1.38 m respectively.

Fig. 1 Cross section of Vransko Bridge

FE Model of the Bridge

The bridge deck is modeled using a C_1 conforming orthotropic rectangular plate element [20]. Both the longitudinal and transverse beam members are modeled using two-noded beam elements with three degrees of freedom per node, one translation and two rotations [21, 22]. The bridge is

discretized into 800 plate elements and 236 beam elements with a total of 861 nodes and 3,444 degrees of freedom. Poisson's ratio of 0.15 and density of $2,400 \text{ kg/m}^3$ were assumed. It was found that Young's moduli, $E_x = 41 \times 10^9 \text{ N/m}^2$ and $E_y = 30 \times 10^9 \text{ N/m}^2$ for the deck and $E_b = 35 \times 10^9 \text{ N/m}^2$ for the longitudinal and diaphragm beams, gave good agreement with the frequencies identified from measurements.

Results

Figure 2 shows the identified forces for some of the nine single vehicle events with the test vehicle traveling in lane 1. For each event, the predicted variation of the forces exerted by the front axle, the rear tandem (axle 2 + axle 3), and the total vehicle force (axle 1 + axle 2 + axle 3) is represented. It is clear that the identified forces generally oscillate about their corresponding static loads represented by horizontal lines at 75.04 (axle 1), 203.55 kN (axle 2 + axle 3) and 278.59 kN (GVW). However, it should be noted that for the first axle of the test vehicle, the identified forces at the start of the bridge are always less than the static axle load. It is only over the period when all three axles are on the bridge that the identified forces for the first axle oscillate about the static axle value. It is difficult to determine the accuracy of the MFI algorithm in the field unless the truck is instrumented. However, some checks are possible. The axle weights and the gross vehicle weights can be obtained by summing the identified forces in the middle 60% [23] of the time history for each axle and averaging the result. These can be compared to the known static values for the test vehicle. The main truck frequencies can also be derived from the time history of the identified forces and the predicted frequencies compared over the range of test runs.

Fig. 2 Identified axle forces versus distance

Table 1 shows the percentage errors for the predicted static weights for each of the runs. In general the percentage error in the static axle weights and the GVW is reasonable, with a maximum error in GVW of 3.8% and a maximum error for axles 2 and 3 of 6.9%. However, there is one event for the vehicle traveling at 11.34 m/s where the error for the first axle is 17%, whilst the error in the gross vehicle is only 0.3%. This equates to an under estimation of the front axle and an over-estimation of the rear axles, this could be due to an error in the calculated vehicle velocity. In each of the test runs, the predicted maximum impact factors (ratio of the maximum applied dynamic force to the

static force) were 1.35, 1.28 and 1.27 for the front axle, rear tandem and total vehicle vertical forces, respectively. The impact factors for the front axle range between 1.10 and 1.35, and for the rear tandem range between 1.08 and 1.28. The average frequencies associated to the identified force histories for the front axle and rear tandem are 3.2 and 3.12 Hz respectively. These are thought to be reasonable frequencies for the body bounce of a rigid three-axle truck with an old steel suspension [24]. The differences between runs are very small which gives confidence in the accuracy of the results. The axle hop frequencies have not been identified, perhaps because they are at a frequency too high to be detected by the algorithm.

Table 1 Percentage error in the static axle weights, impact factors and frequencies for the identified forces

Axle 1			Axles 2+3			GVW		Velocity (m/s)
Percentage error in static weight	Impact factor	Frequency (Hz)	Percentage error in static weight	Impact factor	Frequency (Hz)	Percentage error in static weight	Impact factor	
7.9	1.13	2.9	−1.5	1.12	3.1	1.0	1.09	11.97
−2.0	1.30	3.0	5.0	1.08	3.3	3.0	1.07	11.63
−17.4	1.34	3.1	6.9	1.08	3.0	0.3	1.12	11.31
−3.9	1.26	3.3	3.4	1.09	3.0	1.4	1.12	10.55
10.8	1.03	3.0	−2.7	1.14	3.0	0.9	1.09	13.93
5.0	1.08	3.0	−0.5	1.28	2.7	0.9	1.16	14.84
9.5	1.09	3.0	−4.0	1.22	3.0	−0.3	1.27	18.45
3.2	1.15	3.7	4.0	1.13	3.4	3.8	1.10	19.14
−1.7	1.15	3.8	2.8	1.12	3.7	1.5	1.08	19.50

Conclusions

MFI has been developed in recent years as a theoretical means of finding the complete time history of applied axle forces during the passage of a truck over a bridge. It is tested here using measured field strain data from a B-WIM system. While the method is computationally demanding, it is shown to be feasible for on-site application and the time history of forces can be used to collect information not only on the static axle weights but also on the frequency and amplitude of the dynamic forces.

Acknowledgement The authors would like to express their gratitude for the financial support received from the European 6th Framework Project ARCHES towards this investigation.

References

1. Moses F (1979) Weigh-in-motion system using instrumented bridges. J Transp Eng 105TE3:233–249
2. OBrien EJ, Žnidarič A, Dempsey A (1999) Comparison of two independently developed bridge weigh-in-motion systems. Heavy vehicle systems. Int J Veh Des 61/4:147–162

3. González A, Rowley CW, OBrien EJ (2008) A general solution to the identification of vehicle interaction forces. *Int J Numer Methods Eng* 753:335–354. doi:10.1002/nme.2262
4. Rowley CW OBrien EJ, Gonzalez A (2006) Moving force identification algorithm for two-span continuous bridges using an eigenvalue reduction technique. In: Topping BHV, Montero G, Montenegro R (eds) *Proceedings of the Eighth International Conference on Computational Structures Technology*, Civil-Comp Press, Stirlingshire, UK, paper 142
5. Rowley CW (2007) Moving force identification of axle forces on bridges. Ph.D. thesis, Department of Civil Engineering, University College Dublin, Ireland
6. Law SS, Fang YL (2001) Moving force identification: optimal state estimation approach. *J Sound Vib* 2392:233–254. doi:10.1006/jsvi.2000.3118
7. Trujillo DM (1975) Application of dynamic programming to the general inverse problem. *Int J Numer Methods Eng* 12:613–624. doi:10.1002/nme.1620120406
8. Trujillo DM, Busby HR (1997) *Practical inverse analysis engineering*. CRC, New York
9. Busby HR, Trujillo DM (1995) Optimal regularization of an inverse dynamics problem. *Comput Struct* 63:243–248. doi:10.1016/S0045-7949(96)00340-9
10. Busby HR, Trujillo DM (1986) Solution of an inverse dynamics problem using an eigenvalue reduction technique. *Comput Struct* 25:109–117. doi:10.1016/0045-7949(87)90222-7
11. AdamsR, DoyleJF (2002) Multiple force identification for complex structures. *Exp Mech* 421:25–36. doi:10.1007/BF02411048
12. Tikhonov AN, Arsenin VY (1997) *Solutions of ill-posed problems*. Wiley, New York
13. Zhu XQ, Law SS (2002) Moving loads identification through regularization. *J Eng Mech* 1289:989–1000. doi:10.1061/(ASCE)0733-9399(2002)128:9(989)
14. Law SS, Chan THT, Zhu XQ, Zeng QH (2001) Regularization in moving force identification. *JEngMech* 1272:136–148. doi:10.1061/(ASCE)0733-9399(2001)127:2(136)
15. Lawson CL, Hanson RJ (1974) *Solving least squares problems*. Prentice-Hall, Englewood Cliffs
16. Hansen PC (1992) Analysis of discrete ill-posed problems by means of the L-curve. *SIAM Rev* 344:561–580. doi:10.1137/1034115
17. Hansen PC (1994) Regularization tools: a Matlab package for analysis and solution of discrete ill-posed problems. *Numer Algorithms* 6:1–35. doi:10.1007/BF02149761
18. Hansen PC (1998) Rank-deficient and discrete ill-posed problems. *Numerical aspects of linear inversion*. SIAM Monographs on Mathematical Modelling and Computation, Philadelphia

19. Žnidarič A, Lavrič I, Kalin J (2002) The next generation of bridge weigh-in-motion systems. In: Jacob B, OBrien EJ (eds) Proceedings of the Third International Conference on Weigh-in-Motion Systems (ICWIM3), Orlando, USA, 13–15 May, pp 231–239
20. Bogner FK, Fox RL, Schmit LA (1965) The generation of inter-element-compatible stiffness and mass matrices by the use of interpolation formulae. In: Proceedings of the 1st Conference on Matrix Methods in Structural Mechanics, Air Force Institute of Technology, Wright Patterson Airforce Base, Ohio, October
21. Logan DL (2000) A first course in the finite element method, 3rd edn. Brooks/Cole Thomson Learning, Wadsworth
22. Przemieniecki JS (1968) Theory of matrix structural analysis, 1st edn. McGraw-Hill, New York
23. Chan THT, Yung TH (2003) A theoretical study of force identification using an existing prestressed concrete bridge. Engineering Structures 23:1529–1537
24. OECD (1997) Dynamic interaction of heavy vehicles with roads and bridge. Final report of the Committee, DIVINE Project, Ottawa, Canada, June