Research Repository UCD

Title	Review of Strategies for the Geometric Creation and Population of Urban Microclimate Models
Authors(s)	Laefer, Debra F., Anwar, Muhammad Bashar
Publication date	2012-08-27
Publication information	Laefer, Debra F., and Muhammad Bashar Anwar. "Review of Strategies for the Geometric Creation and Population of Urban Microclimate Models" 5, no. 1 (August 27, 2012).
Publisher	Bentham Science
Item record/more information	http://hdl.handle.net/10197/4873
Publisher's version (DOI)	10.2174/1874942901205010022

Downloaded 2023-04-07T10:52:29Z

The UCD community has made this article openly available. Please share how this access benefits you. Your story matters! (@ucd_oa)

© Some rights reserved. For more information

Review of strategies for the geometric creation and population of urban microclimate models

Dr. Debra F. Laefer*
Head, Urban Modelling Group
University College Dublin
Civil Engineering
Newstead G25
Belfield
Dublin, Ireland 4
353-1-716-3226
353-1-716-3297 (fax)
debra.laefer@ucd.ie

Muhammad Anwar
Visiting Researcher
University College Dublin
Civil Engineering
Newstead G25
Belfield
Dublin, Ireland 4
353-1-716-3226
353-1-716-3297 (fax)
manwar18@gmail.com

Strategies for the geometric creation and population of urban microclimate models

Dr. Debra F. Laefer and Mr. Muhammad Anwar

Abstract

Heightened demand for larger and more accurate microclimate models for heat transfer, pollution accumulation, and wind level prediction has posed new challenges for researchers working in wind tunnels, as well as those employing computational fluid dynamics modelling. Namely, the problem is how to generate geometrically accurate and up to date models inexpensively and quickly without compromising potentially critical details. The problem is an important and growing one, as there is an increased tendency to use such models as the basis for planning permission and long-term policy decisions in urban areas. This review paper traces the recent evolution in the size and detail-level of microclimate models (both physical and numerical) and explains the difficulties of applying the existing technology traditionally adopted in virtual city model creation. Finally, the paper provides an overview of recent innovations in the geometric creation and population of microclimate models to overcome existing documented deficiencies in an absence of architectural detailing in the investigated models through use of aerial laser scanning data.

KEY WORDS: Air Quality; Wind Environment; Urban Heat Island; Microclimate; Laser Scanning; LiDAR

Introduction

Several environmental factors have increased the need for an interest in urban-scale and micro-urban-scale modelling. These include increasing levels of air pollution, global warming, urban wind flow, and the need to limit energy consumption [1, 2]. In each case, there are a variety of factors related to aspects of the built environment of interest to researchers, planners, and engineers. For example, these include the percentage of paved surfaces, the amount of reflective surfaces, the street and building configurations, the level of natural ventilation, and characteristics of the building façades [3].

To attempt to address some of these factors, a variety of strategies have been developed for computational modelling, laboratory testing, and field measurement. However, increasingly there is pressure to incorporate additional factors and to derive more accurate predictions

[4,5]. As such, the approaches used to undertake these activities are changing. To better comprehend traditional and evolving strategies to populate computational and physical models and to monitor field sites, this paper provides a survey of recent models for studying urban heat islands, air pollution dispersion, and wind environment and introduces up and coming technologies that may provide a new and highly cost-efficient means to populate both computational and physical models for microclimate modelling.

To understand new and emerging trends in environmental modelling of urban areas and to identify continuing impediments to more accurate and cost-effective modelling, this paper examines a sampling of newly published research covering the years 2005-2010, with a concentration on the years 2008 to 2010. The main topics included are air quality, wind environment, and urban heat islands. A total of 40 papers are included conveying the efforts of 120 authors from 22 countries.

Air quality modelling has included a variety of concerns. Prominent amongst these are ventilation, contaminant transport, and wind flow; inter-vehicle spacing and vehicle emissions; and pollutant concentration, dispersion, and removal. Wind environment modelling has involved wind direction, urban wind flow, natural indoor ventilation, thermal comfort, and post-occupancy evaluation. The factors of preeminent concern in urban heat island modelling are optimized air flow, urban heat island effect, heat extraction rate, climate change analysis, natural ventilation, draught cooling, heat storage characteristics, outdoor cooling in a hot-arid region, atmospheric heat balance, wind speed, and air temperatures. So although there are a few topics of direct overlap, between the three topics, each area of investigation has a large number of other concerns. What closely unites these three topics is the need to portray aspects of the built environment. This paper investigates how this is currently done with respect to the size, characteristics, and level of detail in a wide range of urban, microclimate models. The aim is to better define the current state-of-the-art as to how the geometries of these urban environmental models are generated and to what extent various elements of the built and natural environment are actually included.

Research Approach

Across the three areas of study, a number of different modelling approaches have been adopted. In air quality and urban heat island investigations, numerical modelling is the

predominant approach with this adopted in 92% of the air quality papers examined and 85% of the urban heat island ones. For wind environment modelling, 76% concentrated on numerical and 24% on physical modelling.

Despite the apparently three-dimensional (3D) nature of each of these 3 problems, of the 40 articles reviewed in this study, 12 relied strictly on a two-dimensional (2D) domain, while 27 worked in the 3D domain, and 1 author compared 3 different methods for modelling wind driven rain without providing domain information. The distribution of articles is shown in figure 1.

Figure 1. Distribution of articles reviewed

The nature of the study areas varied greatly. A total of 24 of them represented a real location(s), while 16 were based on a hypothetical or theoretical locale(s). Within the 40 models, the aspect ratio (height of the building to the width of the street) used by the authors ranged from 0.4 to 8. Six researchers used an aspect ratio of 1. The study area size also greatly varied ranging from 0.014 m² to 1,270 km² in plan and 0.192 m³ to 1,843,200km³ in 3D models (fig. 2).

Figure 2. Area covered in study (2D cases in black and 3D cases in white)

The models ranged greatly in configuration from being comprised of only a single building (e.g. a stadium, a library), to groups of buildings (e.g. an enclosed-arcade market), or selected street canyons (simple ones and those with plantings) and vehicular intersections, up to entire city sections. Of the 40 papers, only 30% specified the number of buildings in the model. In those, the number of buildings specified ranged from 1 to 35 (fig. 3).

Figure 3. Number of buildings around focused area

The scale used in modelling ranged from 1:20 to 1:1000 (Figure 4). Four researchers used a wind tunnel and four others employed physical modelling, along with numerical modelling or used previous physical modelled results from published literature to validate their Computational Fluid Dynamics (CFD) results.

Figure 4. Modelling scale

The models used in different studies are shown in Table 1. In 14 of the standard k- ϵ model was used, in 6 cases the renormalized group k- ϵ model was applied, and in 4 the cases modified k- ϵ model was employed. Another ten models were used either once or twice.

Table 1 Type of model used

Different software packages used in simulation are shown in table 2 below. Fluent was used in 14 cases, and 11 other packages were used only once or twice.

Table 2 Software used in studies

In Figure 5, computational domains are plotted against publication year. The logarithmic scale has been used for Y-axis. The trends show that most of the values are ranging from very small 0.288 to 20E09. In Figure 6 the number of cells/grids is plotted ranging from 65,908 to 500,000,000.

Figure 5. Computational domains

Figure 6. Number of grids

Most of researchers used either a triangular or hexahedral type of grid in modelling (Table 3). Use of hexahedral elements for discretization is most popular and was used in 4 cases. In three cases, triangular elements were used. Other types of elements were reported only once or twice.

Table 3 Type of Grid

The convergence criteria used in different studies varied from 1E-2 to 1E-7, with 37% of the authors using 1E-5 and 25% using 1E-4. Two used the number of time steps as a convergence criterion.

Figure 7. Convergence criteria used in studies

The validation of numerical modelling was done using wind tunnel results either by performing experiments or by comparing with previous studies. There are eight cases in which results of full-scale field measurements were used to validate, and in one case, water channel results were used for validation purposes [6]. In most of the cases, the authors claimed that the results were found in close agreement, but quantification of this claim was rarely provided.

In physical modelling of the wind environment, Kim et al. [7] used 20 points and 2 wind directions, Szucs et al. [8] used 52 points and 3 wind directions, while Yoshie et al. [9] used 78 points and 3 wind directions to take the readings. All of these readings were taken in wind tunnel experiments. Agarwal and Tandon [10] used field measurements for modelling of the urban heat island.

The models were examined for the inclusion of footpaths, curbs, street furniture, vegetation, windows, and architectural elements, as well as material texture, signage, and building setbacks and steps. In general, these features were not modelled, and when they were, only a few attributes were included (Table 4). The notable exceptions were McNabola et al. [11] including footpaths, Priyadarsini et al. [12] modelling the footpaths and setbacks, Gromke et al. [13] incorporating trees, and McNabola et al. [14] modelling the vehicles. Alexandri et al. [15] and Huang et al. [16], (2009) modelled the vegetation and texture, while He et al. [17] modelled vegetation, windows, and building texture.

Table 4 Details of Modelled Elements

Virtual cities and other visualisation-based urban-scale models

What the above survey shows is that the vast majority of environmental models currently being used are extremely idealized. The absence of realistic urban models raises three questions: (1) do highly idealized models compromise the reliability of the outputs; (2) why are more realistic models not being used; and (3) how does one overcome current bottlenecks for rapidly generating accurate, cost-effective models.

Assuming that with every step towards idealization some accuracy is lost, then the goal should be to generate more realistic models. The main obstacle to more realistic modelling is

cost. Given the plethora of highly realistic virtual city models, this may be a surprising conclusion, but a further investigation into the nature, content, and structure of virtual models will show their severe limitations as the basis for in-depth engineering-based modelling.

Originally, Google Earth and other visualisation systems for virtual cities, gaming, and the film industry were mostly inhabited with geo-posters [47], where photo-like images were fitted over generic cubes to give the impression of three-dimensionality, but they were simply immutable images. A more select group of actual 3D models (e.g. Salzburg, Austria and Westport, Ireland) [48] rely on more sophisticated schemes. The most primitive ones (often used in the far-field portion of gaming programs) are instantiated with randomly generated pre-formed structures or other rule grammar- or L-system based solutions [49, 50]. More sophisticated ones use growing techniques. A common one extrudes a building from its planview outline to the maximum elevation of the points within the data set [51]. Beyond this, some virtual cities (e.g. those for tourism) have striven to reflect actual structures. This latest generation relies on more sophisticated processing and rendering. These models are commonly referred to as various Level of Detail (LOD) models, where the most basic ones of LOD1 depict only block models comprised of prismatic building with flat roofs. The more sophisticated ones of LOD2 incorporate differentiated roof structures and thematically differentiated surfaces. The further defined LOD3 models include detailed wall and roof structures, balconies, bay and projections, while LOD4 models focus on interior representations.

Attempts to automatically populate virtual cities efforts incorporates a long history of manual, procedural, and direct methods [52]. Some combine simple 3D models with detailed, real-world texture maps. Jepson et al. [53] overlaid a GIS-based terrain and aerial photographs to position the final models with respect to road networks. A sophisticated version of this is used in the Virtual Dublin project, where 3DS Max is used to model building surface features with digital photographs mapped atop to improve realism [54]. This is one of many approaches as sampled below.

An early attempt employed photogrammetry to reconstruct scene geometry from photographs. The reconstructed models were then textured in a view-dependent fashion, with textures manually selected from the original photographs. Texture warping relied upon computed depth information [55]. Similarly, the MIT City Scanning Project extensively

researched automated data capture for urban simulation [56]. Façade structure and texture were auto-extracted from calibrated pose imagery [57]. This method used sets of images from known positions, which were then correlated to extract vertical façade features. Wang and associates [58] extended this technique with the recovery of microstructure features (e.g. recessed windows) by incorporating multiple images of the same structure from different angles. These techniques relied on calibrated cameras being used from known GPS positions [59]. Similarly, Lee et al. [60] automatically textured building model facades by combining aerial photographs (estimating the camera pose data) and ground-based photographs.

Other techniques have concentrated modelling resources on well-known areas and central landmarks and then relied on procedural generation to artificially produce data to complete more distant geographic areas. In the case of virtual Manhattan, building generation was guided by user input related to building type creation and supplemented by manual building insertion based on six buildings [61]. Alternatively, shape grammars can be exploited to generate building models, allowing rapid development of detailed but varied building models, according to rules derived from the real world [62]. In contrast, building footprints from GIS Landline map data and aerial LiDAR can be combined to extrude buildings, as previously mentioned. Sampling the many available virtual cities shows a wide variety of technological orientations, from strictly manual constructions to grammar-based modelling, and visual, auditory, and haptic response feedback [63]. A unifying characteristic, however, is the immutability of the underlying data set.

In virtual projects, the fact that those systems are static remains a major obstacle for their potential to be developed further as a part of an engineering-oriented, modelling tool. This is because intelligently populating a GIS-based or similar system for high-level engineering analysis requires three things: (1) collecting data in a manner that is timely, cost-efficient, and inherently compatible with the existing underlying system, (2) obtaining data of sufficient accuracy and detail that the resulting information is meaningful to the end user, and (3) manipulating, coding, and archiving the data in a format that critical information can be extracted as relevant input parameters to conduct engineering analyses. The advent of new remote sensing capabilities opens the door to meeting these challenges.

New opportunities in remote sensing data capture

Light Detection and Ranging (LiDAR) is an active remote sensing technology used to collect topographical data [64]. For the aerial version, the data are collected with aircraft-mounted lasers capable of recording elevation measurements at a rate of 5,000-50,000 pulses/sec. The difference in time is measured from when a laser pulse is emitted from a sensor to when the target objects in the path of the laser reflect back the pulse. Using the speed of light, these time measurements can be converted into distance or range [65]. The LiDAR instruments collect elevation data. To make these data spatially relevant, the points' positions must be known. Thus, a high-precision global positioning system (GPS) antenna, mounted on the aircraft, is used to determine the spatial position of each data point. The end product is accurate, geographically registered positions for every data point with respect to longitude, latitude, and elevation from mean sea level (x, y, z) and is typically presented in a plane coordinate system [66]. The terrestrial version of LiDAR uses essentially the same technology but is acquired from the ground with either a stationary or truck-mounted unit.

LiDAR is capable of providing both horizontal and vertical information at high spatial resolutions and vertical accuracies. In general, airborne-based LiDAR data can be within centimetre accuracy and the terrestrial sub-millimetre depending upon the distance, scanning period, and hardware. The extent of aerial LiDAR point density depends on flying height and system dependent factors such as platform velocity, sampling frequency, and field of view [67, 68, and 69]. LiDAR has been used in many applications such as (a) mapping, (b) forestry, (c) coastal engineering, (d) flood plain mapping, (e) disaster damage assessment and response, and (f) urban modelling. A current limitation of LiDAR is that it does not store any topological, shape, or size information of the geographical features scanned. A LiDAR dataset is simply a collection of somewhat randomly distributed 3D points. As feature information is not provided, clever and efficient algorithms are required for element identification depending upon the desired application. Furthermore, attributes must be assigned to groups of points to enable analysis. Recent advances in flight path planning and hardware have radically improved the resolution, as shown in Fig. 8 [70].

(a) LiDAR from a conventional, single path flyover in Dublin study area

(b) LiDAR from a multi-path swath flyover in Dublin study area

Figure 8: Comparison of conventional flight path resolution versus employing techniques developed in Hinks et al. [70].

Divergence

To properly envision the population, construction, and ultimate usage of a large-scale computational urban model, there must first be an understanding of the comparative needs of this type of system versus the previously described virtual cities and visualisation-based, urban-scale models. In a visual model, there may be a great emphasis on architectural details, colour, shading, and texture. Even the surface degradations caused by pollution, rust-staining, efflorescence, plant decay, and wind erosion may be of great importance to be captured to adequately convey the feel of an environment (Table 4). Additionally, building signage, window trimmings in the form of curtains and shades, and other non-structural façade elements may play a crucial role to make an environment appear realistically inhabited. But in the same way that street furniture (i.e. benches, trash bins, and railings), rarely influence engineering assessments and decisions, their absence would leave a visual rendition of an urban environment less convincing. Thus, in the context of a visual model, their importance must be respected, but their absence in an engineering context should not be confused as a deficit in that model. In fact, the converse is most likely true as computational models must in part be considered in terms of processing speed and memory requirement. In current applications, it is not unusual for the single run-time for one large structure to require more than 24 hours. As such, when considering city-scale computational modelling and the requisite computing power, it would appear to be absolutely crucial that extraneous (or at least non-critical) items be excluded.

Table 5: Comparison of the needs of visualisation-based and computationally-based urban models

Of the 14 items listed in Table 5 as possible characteristics or feature content for urban-scale models, nearly two-thirds of them have no commonality between visual and engineering models. Of the other 5 topics, 3 have a low commonality, 1 a medium commonality, and only window detection is of high mutual importance.

What may be difficult to understand at a visceral level is that an urban model may have great functionality without being visually compelling and that the converse is also true. Namely that although an image may have great visual appeal and be highly realistic in all of its aspects, it may have limited, if any, capabilities from an engineering perspective. Presently, the functionality of most virtual or visualisation models is limited to ray tracing activities,

which may be useful for such circumscribed topics as determining cell phone reception. This is not to say that eventually the two concepts may not be completely aligned, but that for the present there is a major disconnect that needs to be acknowledged.

Bottlenecks

Current bottlenecks to generating urban-scale computational models are in large part related the cost of populating such systems with relevant, geo-spatially accurate data. A major challenge is in the automatic identification of individual structures without any a priori knowledge. Although readily identifiable to the human eye, the required data segregation by building without using known building outlines or other means a priori means has proven problematic. Recent efforts by Hinks et al. [70] indicate the strong potential to do this in the near future with a high level of reliability through LiDAR data (Fig. 9).

(a) Results of traditional identification methods for Dublin study area

(b) Results of authors' work in progress methods for Dublin study area

Fig. 9: Comparison of the results of traditional techniques versus work in progress techniques by Hinks et al. [70] for automatic building identification, with results evident by the flood-filled structures.

The LiDAR data outlined in the previous section is not a panacea. It cannot capture the interior of structures, nor identify the sizing and exact positioning of structural members, nor categorize the construction materials. However the existing technology could provide a major cost-savings in terms of identifying the position, outline, and major features of the buildings, and in those respects is no different than the role of the traditional survey team sent to document existing structures in-situ.

Discussion

What is envisioned is a pipeline using remote sensing to automatically and seamlessly to generate neutral files that can be read by commercial computational modelling programmes to generate solid models that converge without any further intervention and generate reasonable results on a city-scale. The fundamentals of such a pipelines are depicted in Fig. 10. These encompass only the items listed as high priority for computational modelling in Table 5. The technology is likely to prove most readily transferable in city-scale modeling of air pollution. For instance, in the European Union funded project Population Exposure to Air Pollutants in Europe (PEOPLE) simultaneous diffusive measurements of outdoor, indoor and human exposure benzene concentrations were made in 6 European cities. In that study, a

linear relationship was evident between ambient levels and human exposure [72]. Similarly real-time concentrations of PM₁₀ were monitored to examine the influence of daily activities and locations on the personal exposure of city centre office workers to air pollution to compare various filter separation and frequency analysis techniques in success of segregating background concentration from real-time personal exposure data [73]. These studies raise the question of how the built environment can be geometrically modified to lower ambient levels. More realistic 3D computational modeling would support such investigation.

Fig. 10: LiDAR processing from terrestrial point cloud data into a commercial programme's solid model [71]

Conclusions

In this study, recently published strategies for the creation and population of urban microclimate models have been reviewed in the context of physical and numerical modelling for air quality, wind environments, and urban heat islands. The trends showed a predominance for numerical modelling with the study area covered by different authors varying from single buildings to entire city sections. The scale used in modelling ranged from 1:20 to 1:1000. The standard k- ϵ model was most widely used model, and Fluent was the mostly commonly applied commercial code. In numerical modelling researchers used a wide range of computational domains, number of grids, element types, and convergence criteria. In physical modelling different wind directions and number of point for readings were variously selected. This paper outlines the fundamental incompatibility between existing urban-scale models developed for visualisation and those that will be increasingly needed for computational modelling in the twenty-first century. The critical characteristics required for these future systems are introduced and a portion of the required pipeline to achieve this in an entirely automated manner is introduced using aerial LiDAR as the main component of its input data.

ACKNOWLEDGMENTS

Thanks to Dr. Agota Szucs and Ms. Orlaith O'Brien who helped during the early stages of this work. Also thanks to the authors of the research articles who provided extra information wherever it was needed. Support for this work was generously provided by Science Foundation Ireland, Grant 05/PICA/I830 and the Environmental Protection Agency Grant 2005-CD-U1-M1.

REFERENCES

- [1] Okeil, A. A holistic approach to energy efficient building forms. *Energy and Buildings* 2009; 42(9): 1437-1444.
- [2] Han J, Yang W, Zhou J, Zhang G, Zhang Q, Moschandreas DJ. A comparative analysis of urban and rural residential thermal comfort under natural ventilation environment. *Energy and Buildings* 2009; 41(2): 139-145.
- [3] Kantzioura P, Kosmopoulos S, Zoras S. Urban surface temperature and microclimate measurements in Thessaloniki. *Energy and Buildings* 2012; 44(1): 63-72.
- [4] Stazi F, Di Perna C, Munafò P. Durability of 20-year-old external insulation and assessment of various types of retrofitting to meet new energy regulations. *Energy and Buildings* 2009; 41(7): 721-731.
- [5] Martinaitis V, Bieksa D, Miseviciute V. Degree-days for the exergy analysis of buildings. *Energy and Buildings* 2010; 42 (7): 1063-1069.
- [6] Cheng WC, Liu CH, Leung DYC. On the correlation of air and pollutant exchange for street canyons in combined wind-buoyancy-driven flow. *Atmospheric Environment* 2009; 43: 3682-90.
- [7] Kim K, Kim K, Kim BS. A wind tunnel experiment and CFD analysis on airflow performance of enclosed-arcade markets in Korea. *Building and Environment* 2009; 45: 1329-38.
- [8] Szucs A, Moreau S, Allard F. Spectators' aerothermal comfort assessment method in stadia". *Building and Environment* 2007; 42: 2227-40.
- [9] Yoshie R, Mochida A, Tominaga Y, Kataoka H, Yoshikawa M. Cross comparisons of CFD prediction for wind environment at pedestrian level around buildings in Sixth Asia-Pacific Conference on Wind Engineering (APCWE-VI) Seoul, Korea, 2005; 2661-70.
- [10] Agarwal M, Tandon A. Modeling of the urban heat island in the form of mesoscale wind and of its effect on air pollution dispersal. *Applied Mathematical Modelling* 2009; 34: 2520-30.
- [11] McNabola A, Broderick BM, Gill LW. A numerical investigation of the impact of low boundary walls on pedestrian exposure to air pollutants in urban street canyons. *Science of the Total Environment* 2008; 407: 760-69.
- [12] Priyadarsini R, Hien WN, David CKW. Microclimatic modeling of the urban thermal environment of Singapore to mitigate urban heat island. *Solar Energy* 2008; 82: 727-45.
- [13] Gromke C, Buccolieri R., Di S S, Ruck B. Dispersion study in a street canyon with tree planting by means of wind tunnel and numerical investigations–Evaluation of CFD data with experimental data. *Atmospheric Environment* 2008; 42: 8640-50.

- [14] McNabola A, Broderick BM, Gill LW. The impacts of inter-vehicle spacing on in-vehicle air pollution concentrations in idling urban traffic conditions. *Transportation Research Part 2009*; D 14: 567-75.
- [15] Alexandri E, Jones P. Temperature decreases in an urban canyon due to green walls and green roofs in diverse climates. *Building and Environment* 2008; 43: 480-93.
- [16] Huang Y, Hu X, Zeng N. Impact of wedge-shaped roofs on airflow and pollutant dispersion inside urban street canyons". *Building and Environment* 2009; 44: 2335–2347.
- [17] He J, Hoyano A, Asawa T. A numerical simulation tool for predicting the impact of outdoor thermal environment on building energy performance. *Applied Energy* 2009; 86: 1596-1605.
- [18] Abuku M, Blocken B, Nore K, Thue JV, Carmeliet J, Roels S. On the validity of numerical wind-driven rain simulation on a rectangular low-rise building under various oblique winds. *Building and Environment* 2008; 44: 621-632.
- [19] Blocken B, Carmeliet J. Overview of three state-of-the-art wind-driven rain assessment models and comparison based on model theory. *Building and Environment* 2009; 45: 691-703.
- [20] Carpentieri M, Robins AG. Wind tunnel experiments of flow and dispersion in a real urban area. *The Seventh International Conference on Urban Climate*, 2009, Yokohama, Japan; 1-4.
- [21] Cheng WC, Liu CH, Leung DY. Computational formulation for the evaluation of street canyon ventilation and pollutant removal performance. *Atmospheric Environment* 2008; 42: 9041-51.
- [22] Coirier WJ, Fricker DM, Furmanczyk M, Kim S. A Computational fluid dynamics approach for urban area transport and dispersion modeling. *Environmental Fluid Mechanics* 2005; 5: 443-79.
- [23] Hooff TV, Blocken B. Coupled urban wind flow and indoor natural ventilation modelling on a high-resolution grid: A case study for the Amsterdam Arena stadium. *Environmental Modelling & Software* 2009; 25: 51-65.
- [24] Hooff TV, Blocken B. On the effect of wind direction and urban surroundings on natural ventilation of a large semi-enclosed stadium. *Computers & Fluids* 2010; 39: 1146-55.
- [25] Hua CH, Wang F. Using a CFD approach for the study of street-level winds in a built-up area. *Building and Environment* 2005; 40: 617-31.
- [26] Huang Y, Hu X, Zeng N. Impact of wedge-shaped roofs on airflow and pollutant dispersion inside urban street canyons. *Building and Environment* 2009; 44: 2335-47.
- [27] Huang JM, Ooka R, Okada A, Omori A, Huang H. The effects of urban heat island mitigation strategies on the outdoor thermal environment in central Tokyo – a numerical

simulation. The Seventh Asia-Pacific Conference on Wind Engineering. Taiwan: Taipei; 2009; 272-279.

[28] Huang H, Ooka H, Kato S. Urban thermal environment measurements and numerical simulation for an actual complex urban area covering a large district heating and cooling system in summer. *Atmospheric Environment* 2005; 39: 6362-75.

[29] Li K, Yu Z. Comparative and Combinative Study of Urban Heat Island in Wuhan City with Remote Sensing and CFD Simulation. *Sensors* 2008; 8: 6692-6703.

[30] Memon RA, Leung DY, Liu CH. Effects of building aspect ratio and wind speed on air temperatures in urban-like street canyons. *Building and Environment* 2009; 45: 176-88.

[31] Meyn SK, Oke TR. Heat fluxes through roofs and their relevance to estimates of urban heat storage. *Energy and Buildings* 2009; 41: 745-52.

[32] Neofytou P, Venetsanos AG, Vlachogiannis D, Bartzis JG, Scaperdas A. CFD simulations of the wind environment around an airport terminal building. *Environmental Modelling & Software* 2006; 21: 520-24.

[33] Oguro M, Morikawa Y, Murakami S, Matsunawa K, Mochida A, Hayashi H. Development of a wind environment database in Tokyo for a comprehensive assessment system for heat island relaxation measures. *Journal of Wind Engineering and Industrial Aerodynamics* 2008; 96: 1591-1602.

[34] Oliveria P, Gonalves HJP, Ferrao PMC. Numerical analysis of the street canyon thermal conductance to improve urban design and climate. *Building and Environment* 2009; 44: 177-87.

[35] Oxizidis S, Dudek AV, Papadopoulos AM. A computational method to assess the impact of urban climate on buildings using modeled climatic data. *Energy and Buildings* 2008; 40: 215-23.

[36] Parra MA, Santiago JL, Martín F, Martilli A, and Santamaría JM. A methodology to urban air quality assessment during large time periods of winter using computational fluid dynamic models. *Atmospheric Environment* 2010; 44: 2089-97.

[37] Sabatino SD, Buccolieri R, Pulvirenti B, Britter RE. Flow and pollutant dispersion in street canyons using FLUENT and ADMS. *Urban Environmental Model Assessment* 2008; 13: 369-81.

[38] Sato T, Murakami S, Ooka R, Yoshida S. Analysis of regional characteristics of the atmospheric heat balance in the Tokyo metropolitan area in summer. *Journal of Wind Engineering and Industrial Aerodynamics* 2008; 96: 1640-54.

[39] Shashua-Bar L, Pearlmutter D, Erell E. The cooling efficiency of urban landscape strategies in a hot dry climate. *Landscape and Urban Planning* 2009; 92: 179-86.

[40] Short CA, Cook MJ, Woods A. Low energy ventilation and cooling within an urban heat island. *Renewable Energy* 2009; 34: 2022-29.

- [41] Tewari M, Kusaka H, Chen F, Coirier WJ, Kim S, Wyszogrodzki AA, Warner TT. Impact of coupling a microscale computational fluid dynamics model with a mesoscale model on urban scale contaminant transport and dispersion. *Atmospheric Research* 2010; 96: 656-64.
- [42] Wakes SJ, Maegli T, Dickinson KJ, Hilton MJ. Numerical modelling of wind flow over a complex topography. *Environmental Modelling & Software* 2009; 25: 237-47.
- [43] Wang P, Mu H. Numerical simulation of pollutant flow and dispersion in different street layouts. *International Journal of Environmental Studies* 2010; 67(2): 155-67.
- [44] Xiao-min X, Jia-song W, Zhen H. Traffic emission transportation in street canyons. *Journal of Hydrodynamics* 2008; 21(1): 108-17.
- [45] Yassin MF, Kellnerova R, Janour Z. Impact of street intersections on air quality in an urban environment. *Atmospheric Environment* 2008; 42: 4948-63.
- [46] Zhang A, Gao C, Zhang L. Numerical simulation of the wind field around different building arrangements. *Journal of Wind Engineering and Industrial Aerodynamics* 2005; 93: 891-904.
- [47] Dobbyn S, Hamill J, O'Connor K, O'Sullivan C. Geopostors: A Real-Time Geometry/Impostor Crowd Rendering System. *Proceedings of the ACM SIGGRAPH Symposium on Interactive 3D Graphics and Games*. Washington D.C, USA; 2005: 95-102.
- [48] Westport 2012. Retrieved June 1, 2012. Available from: <http://www.mayo-ireland.ie/virtualtours/westport.htm>.
- [49] Parish Y, Müller P. Procedural Modelling of Cities. *Computer Graphics, Proc. SIGGRAPH'2001*. Los Angeles, CA, USA, 2001: 301-308.
- [50] Watson B, Müller P, Wonka P, Sexton C, Veryovka O, Fuller A. procedural urban modeling in practice. *Procedural Methods for Urban Modeling Tutorial IEEE Computer Graphics and Applications*, May/June 2008: 18-26.
- [51] Wonka P, Wimmer M, Sillion F, Ribarsky W. Instant architecture. *ACM Transactions on Graphics* 2003; 22(3): 669-77.
- [52] Maas HG, Vosselman G. Two algorithms for extracting building models from raw laser altimetry data. *ISPRS Journal of Photogrammetry and Remote Sensing* 1999; 54(2-3): 153-63.
- [53] Jepson W, Liggett R, Friedman S. Virtual modelling of urban environments. *Presence* 1996; 5(1): 83-95.
- [54] Autodesk 2011. Retrieved on June 1, 2012. Available from: <http://usa.autodesk.com/adsk/servlet/index?siteID=123112&id=565930232> texture warping.

- [55] Debevec PE, Taylor CJ, Malik J. Modelling and rendering architecture from photographs: a hybrid geometry- and image-based approach. Computer Graphics; Proc. SIGGRAPH 1996. New Orleans, LA, USA, 1996: 11-20.
- [56] Teller S. 2005 MIT CSAIL MIT City Scanning Project, 2005, Retrieved on June 1, 2012. Available from: <http://www.city.lcs.mit.edu/city.html>.
- [57] Coorg S. Pose Imagery and automated three-dimensional modeling of urban environments, PhD Thesis. MIT 1998.
- [58] Wang X, Totaro S, Taillandier G, Hanson A., Teller S. Recovering Façade Texture and Microstructure from Real-World Images. Proc. 2nd International Workshop on Texture Analysis and Synthesis. Copenhagen, Denmark, 2002; 145-149.
- [59] Teller S. Visibility computation in densely occluded polyhedral environments, PhD Thesis, University of California Berkeley 1992.
- [60] Lee SC, Jung SK, Nevatia R. Automatic integration of façade textures into 3D building models with a projective geometry based line clustering. Computer Graphics Forum 2002; 21(3): 677-86.
- [61] Sun J, Baciú G, Yu X, Green M. Template-based generation of road networks for virtual city modelling. Proc. ACM VRST, Shatin, Hong Kong, 2002; 33-40.
- [62] Yap C, Bierman H, Hertzman A, Li C, Meyer J, Pao HK, Paxia TA. A different Manhattan project: automatic statistical model generation. Proc. SPIE Visualization and Data Analysis. San Jose, CA, USA, 2002; 259-68.
- [63] Laycock RG, Day AM. Automatically generating large urban environments based on the footprint data of buildings. SM'03: Proceedings of the 8th ACM Symposium on Solid Modelling and Applications, University of Washington, Seattle, Washington, USA, 2003; 346-51.
- [64] Van Veen HA, Distler HC, Distler HK, Braun SJ, Bühlhoff HH. Navigating through a virtual city: using virtual reality technology to study human action and perception. Future Generation Computer Systems 1998; 14(3-4): 231-42.
- [65] NOAA 2003. About LIDAR Data. Retrieved on June 1, 2012. Available from <http://www.csc.noaa.gov/products/sccoasts/html/tutlid.htm>
- [66] Lim K, Treitz P, Groot A, St-Onge B. Estimation of individual tree heights using LIDAR remote sensing. Proceedings of the 23rd Canadian Symposium on Remote Sensing. Canadian Aeronautics and Space Institute, Ottawa, Canada, 2001: 251-258.
- [67] Axelsson P. Processing of laser scanner data – algorithms and applications. ISPRS Journal of Photogrammetry and Remote Sensing 1999; 54(2-3): 138-47.
- [68] Baltsavias M. Airborne laser scanning- basic relations and formulas. ISPRS Journal of Photogrammetry and Remote Sensing 1999; 54(2-3): 199-214.

[69] Airborne-lasermapping 2003. Airborne-lasermapping '03 Overview - An Emerging Survey Technology. Retrieved on June 1, 2012. Available from: <http://www.airbornelaser-mapping.com/ALMSkinny.html>

[70] Hinks T, Carr H, Laefer DF. Flight optimization algorithms for aerial LiDAR capture for urban infrastructure model generation. *Journal of Computing in Civil Engineering* 2009; 23(6): 330-9.

[71] Truong-Hong L. Automatic generation of solid models from LiDAR data. Ph.D. Thesis. University College Dublin, Ireland, 2011.

[72] Ballesta PP, Field, RA, Connolly, R, Cao N, Caracena AB, De Saeger E. Population exposure to benzene: One day cross-sections in six European cities. *Atmospheric Environment* 2006, 40(18): 3355-3366.

[73] McNabola A, McCreddin A, Gill LW, Broderick BM. Analysis of the relationship between urban background air pollution concentrations and the personal exposure of office workers in Dublin, Ireland, using baseline separation techniques. *Atmospheric Pollution Research* 2011, 2(1): 80-88.

Fig. (1). Distribution of articles reviewed.

Fig. (2). Area covered in study (2D cases in black and 3D cases in white).

Fig. (3). Number of buildings around focused area.

Fig. (4). Modeling scale.

Table 1. Type of Model Used

Model Type	Times Appearing in Articles
Standard k- model	14
Renormalized group k- model	6
Modified k- models	4
Realizable k- model	2
Reynolds Stress Model	1
CFD-Urban-model	1
Modified RNG turbulence	1
Large eddy simulation model	1
Direct simulation method	1
Implicit Crank–Nicolson	1
STAR model	1
Algebraic second-moment closure model	1
Advection diffusion	1

Table 2. Software Used in Studies

Software	Used in Articles
Fluent	14
CFX	2
Phoenix	2
Star CD	2
CFD-Urban	1
STAR	1
WinAir4	1
EnergyPlus	1
TEACH	1
ADREA-HF	1
3-D CFD	1
CFD-ACE+	1

Fig. (5). Computational domains.

Fig. (6). Number of grids.

Table 3. Type of Grid

Element Type	Used in Articles
Hexaahedral	4
Triangular	3
Irregular Grid	2
Quadtree-Prismatic/Octree	1
Quadrilateral	1
Unstructured Tetrahedral	2
Structured Rectangular	1

Fig. (7). Convergence criteria used in studies.

Review of strategies for the creation and population of urban microclimate models

Dr. Debra F. Laefer*
 Head, Urban Modelling Group
 University College Dublin
 Civil Engineering
 Newstead G25
 Belfield
 Dublin, Ireland 4
 353-1-716-3226
 353-1-716-3297 (fax)
 debra.laefer@ucd.ie

Muhammad Anwar
 Visiting Researcher
 University College Dublin
 Civil Engineering
 Newstead G25
 Belfield
 Dublin, Ireland 4
 353-1-716-3226
 353-1-716-3297 (fax)
 manwar18@gmail.com

Strategies for the creation and population of urban microclimate models

Dr. Debra F. Laefer and Mr. Muhammad Anwar

Abstract

Heightened demand for larger and more accurate microclimate models for heat transfer, pollution accumulation, and wind level prediction has posed new challenges for researchers working in wind tunnels, as well as those employing computational fluid dynamics modelling. Namely, the problem is how to generate geometrically accurate and up to date models inexpensively and quickly without compromising potentially critical details. The problem is an important and growing one, as there is an increased tendency to use such models as the basis for planning permission and long-term policy decisions in urban areas. This review paper traces the recent evolution in the size and detail-level of microclimate models (both physical and numerical) and explains the difficulties of applying existing technology traditionally adopted in virtual city model creation. Finally, the paper provides an overview of recent innovations in the creation and population of microclimate models to overcome existing documented deficiencies in an absence of architectural detailing in the investigated models through use of aerial laser scanning data.

KEY WORDS: Air Quality; Wind Environment; Urban Heat Island; Microclimate; Laser Scanning; LiDAR

Introduction

Several environmental factors have increased the need for an interest in urban-scale and micro-urban-scale modelling. These include increasing levels of air pollution, global warming, urban wind flow, and the need to limit energy consumption [1, 2]. In each case, there are a variety of factors related to aspects of the built environment of interest to researchers, planners, and engineers. For example, these include the percentage of paved surfaces, the amount of reflective surfaces, the street and building configurations, the level of natural ventilation, and characteristics of the building façades [3].

To attempt to address some of these factors, a variety of strategies have been developed for computational modelling, laboratory testing, and field measurement. However, increasingly there is pressure to incorporate additional factors and to derive more accurate predictions [4,5]. As such, the approaches used to undertake these activities are changing. To better

comprehend traditional and evolving strategies to populate computational and physical models and to monitor field sites, this paper provides a survey of recent models for studying urban heat islands, air pollution dispersion, and wind environment and introduces up and coming technologies that may provide a new and highly cost-efficient means to populate both computational and physical models for microclimate modelling.

To understand new and emerging trends in environmental modelling of urban areas and to identify continuing impediments to more accurate and cost-effective modelling, this paper examines a sampling of newly published research covering the years 2005-2010, with a concentration on the years 2008 to 2010. The main topics included are air quality, wind environment, and urban heat islands. A total of 40 papers are included conveying the efforts of 120 authors from 22 countries.

Air quality modelling has included a variety of concerns. Prominent amongst these are ventilation, contaminant transport, and wind flow, inter-vehicle spacing and vehicle emissions, and pollutant concentration, dispersion, and removal. Wind environment modelling has involved wind direction, urban wind flow, natural indoor ventilation, thermal comfort, and post-occupancy evaluation. The factors of preeminent concern in urban heat island modelling are optimized air flow, urban heat island effect, heat extraction rate, climate change analysis, natural ventilation, downdraught cooling, heat storage characteristics, outdoor cooling in a hot-arid region, atmospheric heat balance, wind speed, and air temperatures. So although there are a few topics of direct overlap, between the three topics, each area of investigation has a large number of other concerns. What closely unites these three topics is the need to portray aspects of the built environment. This paper investigates how this is currently done with respect to the size, characteristics, and level of detail in a wide range of urban, microclimate models. The aim is to better define the current state-of-the-art as to how these urban environmental models are generated and to what extent various elements of the built and natural environment are actually included.

Research Approach

Across the three areas of study, a number of different modelling approaches have been adopted. In air quality and urban heat island investigations, numerical modelling is the predominant approach with this adopted in 92% of the air quality papers examined and 85%

of the urban heat island ones. For wind environment modelling, 76% concentrated on numerical and 24% on physical modelling.

Despite the apparently three-dimensional (3D) nature of each of these 3 problems, of the 40 articles reviewed in this study, 12 relied strictly on a two-dimensional (2D) domain, while 27 worked in the 3D domain, and 1 author compared 3 different methods for modelling wind driven rain without providing domain information. The distribution of articles is shown in figure 1.

Figure 1. Distribution of articles reviewed

The nature of the study areas varied greatly. A total of 24 of them represented a real location(s), while 16 were based on a hypothetical or theoretical locale(s). Within the 40 models, the aspect ratio (height of the building to the width of the street) used by the authors ranged from 0.4 to 8. Six researchers used an aspect ratio of 1. The study area size also greatly varied ranging from 0.014 m² to 1,270 km² in plan and 0.192 m³ to 1,843,200km³ in 3D models (fig. 2).

Figure 2. Area covered in study (2D cases in black and 3D cases in white)

The models ranged greatly in configuration from being comprised of only a single building (e.g. a stadium, a library), to groups of buildings (e.g. an enclosed-arcade market), or selected street canyons (simple ones and those with plantings) and vehicular intersections, up to entire city sections. Of the 40 papers, only 30% specified the number of buildings in the model. In those, the number of buildings specified ranged from 1 to 35 (fig. 3).

Figure 3. Number of buildings around focused area

The scale used in modelling ranged from 1:20 to 1:1000 (Figure 4). Four researchers used a wind tunnel and four others employed physical modelling, along with numerical modelling or used previous physical modelled results from published literature to validate their Computational Fluid Dynamics (CFD) results.

Figure 4. Modelling scale

The models used in different studies are shown in Table 1. In 14, the standard k-ε model was used, in 6 cases the renormalized group k-ε model, and in 4 cases modified k-ε model was employed. Another ten models were used either once or twice.

Table 1 Type of model used

Model Type	Times Appearing in Articles
Standard k- ϵ model	14
Renormalized group k- ϵ model	6
Modified k- ϵ models	4
Realizable k- ϵ model	2
Reynolds Stress Model	1
CFD-Urban-model	1
Modified RNG turbulence	1
Large eddy simulation model	1
Direct simulation method	1
Implicit Crank–Nicolson	1
STAR model	1
Algebraic second-moment closure model	1
Advection diffusion	1

Different software packages used in simulation are shown in table 2 below. Fluent was used in 14 cases, and 11 other packages we used once or twice.

Table 2 Software used in studies

Software	Used in Articles
Fluent	14
CFX	2
Phoenics	2
Star CD	2
CFD-Urban	1
STAR	1
WinAir4	1
EnergyPlus	1
TEACH	1
ADREA-HF	1
3-D CFD	1
CFD-ACE+	1

In Figure 5, computational domains are plotted against publication year. The logarithmic scale has been used for Y-axis. The trends show that most of the values are ranging from very small 0.288 to 20E09. In Figure 6 the number of cells/grids is plotted ranging from 65,908 to 500,000,000.

Figure 5. Computational domains

Figure 6. Number of grids

Most of researchers used either a triangular or hexahedral type of grid in modelling (Table 3). Use of hexahedral elements for discretization is most popular and has been used in 4 cases. In three cases, triangular elements were used. Other types of elements were reported only once or twice.

Table 3 Type of Grid

Element Type	Used in Articles
Hexaahedral	4
Triangular	3
Irregular Grid	2
Quadtree-Prismatic/Octree	1
Quadrilateral	1
Unstructured Tetrahedral	2
Structured Rectangular	1

The convergence criteria used in different studies varied from $1\text{E}-2$ to $1\text{E}-7$, with 37% of the authors using $1\text{E}-5$ and 25% using $1\text{E}-4$. Two used the number of time steps as a convergence criterion.

Figure 7. Convergence criteria used in studies

The validation of numerical modelling was done using wind tunnel results either by performing experiments or by comparing with previous studies. There are eight cases in which results of full-scale field measurements were used to validate, and in one case, water channel results were used for validation purposes [6]. In most of the cases, the authors claimed that the results were found in close agreement, but quantification of this claim was rarely provided.

In physical modelling of the wind environment, Kim et al. [7] used 20 points and 2 wind directions, Szucs et al. [8] used 52 points and 3 wind directions, while Yoshie et al. [9] used 78 points and 3 wind directions to take the readings. All of these readings were taken in wind tunnel experiments. Agarwal and Tandon [10] used field measurements for modelling of the urban heat island.

The models were examined for the inclusion of footpaths, curbs, street furniture, vegetation, windows, and architectural elements, as well as material texture, signage, and building setbacks and steps. In general, these features were not modelled, and when they were, only a few attributes were included (Table 4). The notable exceptions were McNabola et al. [11] including footpaths, Priyadarsini et al. [12] modelling the footpaths and setbacks, Gromke et al. [13] incorporating trees, and McNabola et al. [14] modelling the vehicles. Alexandri et al.

[15] and Huang et al. [16], (2009) modelled the vegetation and texture, He et al. [17] modelled vegetation, windows and texture of buildings

Table 4 Details of Modelled Element (see next page)

Paper	Footpath	Curbs	Vehicles	Street Furniture	Vegetation	Windows	Architectural Elements	Texture	Signage	Steps	Setbacks
Abuku et al. [18]	No	No	No	No	No	No	No	No	No	No	No
Agarwal et al. [10]	No	No	No	No	No	No	No	No	No	No	No
Alexandri et al. [15]	No	No	No	No	Yes	No	No	Yes	No	No	No
Blocken and Carmeliet [19]	No	No	No	No	No	No	No	No	No	No	No
Carpentieri and Robins [20]	No	No	No	No	No	No	No	No	No	No	No
Cheng et al. [6]	No	No	No	No	No	No	No	No	No	No	No
Cheng et al. [21]	No	No	No	No	No	No	No	No	No	No	No
Coirier et al. [22]	No	No	No	No	No	No	No	No	No	No	No
Gromke et al. [13]	No	No	No	No	Yes	No	No	No	No	No	No
He et al. [17]	No	No	No	No	Yes	Yes	No	Yes	No	No	No
Hooff and Blocken [23]	No	No	No	No	No	No	Yes	No	No	No	No
Hooff and Blocken. [24]	No	No	No	No	No	No	Yes	No	No	No	No
Hua & Wang [25]	No	No	No	No	No	No	No	No	No	No	No
Huang et al. [26]	No	No	No	No	No	No	No	No	No	No	No
Huang et al. [27]	No	No	No	No	Yes	No	No	Yes	No	No	No
Huang et al. [28]	No	No	No	No	No	No	No	No	No	No	No
Kim et al. [7]	No	No	No	No	No	No	No	No	No	No	No
Li & Yu [29]	No	No	No	No	No	No	No	No	No	No	No
McNabola et al. [11]	Yes	No	No	No	No	No	No	No	No	No	No
McNabola et al. [14]	No	No	Yes	No	No	No	No	No	No	No	No
Memon et al. [20]	Yes	No	No	No	No	No	No	No	No	No	Yes
Meyn and Oke [31]	No	No	No	No	No	No	No	No	No	No	No
Neofytou et al. [32]	No	No	No	No	No	No	No	No	No	No	No
Oguro et al. [33]	No	No	No	No	No	No	No	No	No	No	No
Oliveira et al. [34]	No	No	No	No	No	No	No	No	No	No	No
Oxizidis et al. [35]	No	No	No	No	No	No	No	No	No	No	No
Parra et al. [36]	No	No	No	No	No	No	No	No	No	No	No
Priyadarsini et al. [12]	No	No	No	No	No	No	No	Yes	No	No	No
Sabatino et al. [37]	No	No	No	No	No	No	No	No	No	No	No
Satoa et al. [38]	No	No	No	No	No	No	No	No	No	No	No
Shashua-Bar et al. [39]	No	No	No	No	Yes	No	No	No	No	No	No
Short et al. [40]	No	No	No	No	No	No	No	No	No	No	No
Szucs et al. [8]	No	No	No	No	No	No	No	No	No	No	No
Tewari et al. [41]	No	No	No	No	No	No	No	No	No	No	No
Wakes. et al. [42]	No	No	No	No	No	No	No	No	No	No	No
Wang and Mu [43]	No	No	No	No	No	No	No	No	No	No	No
Xiao-min et al. [44]	No	No	No	No	No	No	No	No	No	No	No
Yassin et al. [45]	No	No	No	No	No	No	No	No	No	No	No
Yoshie et al. [9]	No	No	No	No	No	No	No	No	No	No	No
Zhang et al. [46]	No	No	No	No	No	No	No	No	No	No	No

Virtual cities and other visualisation-based urban-scale models

What the above survey shows is that the vast majority of environmental models currently being used are extremely idealized. The absence of realistic urban models raises three questions: (1) do highly idealized models compromise the reliability of the outputs; (2) why are more realistic models not being used; and (3) how does one overcome current bottlenecks for rapidly generating accurate, cost-effective models.

Assuming that with every step towards idealization some accuracy is lost, then the goal should be to generate more realistic models. The main obstacle to more realistic modelling is cost. Given the plethora of highly realistic virtual city models, this may be a surprising conclusion, but a further investigation into the nature, content, and structure of virtual models will show their severe limitations as the basis for in-depth engineering-based modelling.

Originally, Google Earth and other visualisation systems for virtual cities, gaming, and the film industry were mostly inhabited with geo-posters [47], where photo-like images were fitted over generic cubes to give the impression of three-dimensionality, but they were simply immutable images. A more select group of actual 3D models (e.g. Salzburg, Austria and Westport, Ireland) [48] rely on more sophisticated schemes. The most primitive ones (often used in the far-field portion of gaming programs) are instantiated with randomly generated pre-formed structures or other rule grammar- or L-system based solutions [49, 50]. More sophisticated ones use growing techniques. A common one extrudes a building from its planview outline to the maximum elevation of the points within the data set [51]. Beyond this, some virtual cities (e.g. those for tourism) have striven to reflect actual structures. This latest generation relies on more sophisticated processing and rendering. These models are commonly referred to as various Level of Detail (LOD) models, where the most basic ones of LOD1 depict only block models comprised of prismatic building with flat roofs. The more sophisticated ones of LOD2 incorporate differentiated roof structures and thematically differentiated surfaces. The further defined LOD3 models include detailed wall and roof structures, balconies, bay and projections, while LOD4 models focus on interior representations.

Attempts to automatically populate virtual cities efforts incorporates a long history of manual, procedural, and direct methods [52]. Some combine simple 3D models with detailed,

real-world texture maps. Jepson et al. [53] overlaid a GIS-based terrain and aerial photographs to position the final models with respect to road networks. A sophisticated version of this is used in the Virtual Dublin project, where 3DS Max is used to model building surface features with digital photographs mapped atop to improve realism [54]. This is one of many approaches as sampled below.

An early attempt employed photogrammetry to reconstruct scene geometry from photographs. The reconstructed models were then textured in a view-dependent fashion, with textures manually selected from the original photographs. Texture warping relied upon computed depth information [55]. Similarly, the MIT City Scanning Project extensively researched automated data capture for urban simulation [56]. Façade structure and texture were auto-extracted from calibrated pose imagery [57]. This method used sets of images from known positions, which were then correlated to extract vertical façade features. Wang and associates [58] extended this technique with the recovery of microstructure features (e.g. recessed windows) by incorporating multiple images of the same structure from different angles. These techniques relied on calibrated cameras being used from known GPS positions [59]. Similarly, Lee et al. [60] automatically textured building model facades by combining aerial photographs (estimating the camera pose data) and ground-based photographs.

Other techniques have concentrated modelling resources on well-known areas and central landmarks and then relied on procedural generation to artificially generate data to complete more distant geographic areas. In the case of virtual Manhattan, building generation was guided by user input related to building type creation and supplemented by manual building insertion based on six buildings [61]. Alternatively, shape grammars can be exploited to generate building models, allowing rapid development of detailed but varied building models, according to rules derived from the real world [62]. In contrast, building footprints from GIS Landline map data and aerial LiDAR can be combined to extrude buildings, as previously mentioned. Sampling the many available virtual cities shows a wide variety of technological orientations, from strictly manual constructions to grammar-based modelling, and visual, auditory, and haptic response feedback [63]. A unifying characteristic, however, is the immutability of the underlying data set.

In virtual projects, the fact that those systems are static remains a major obstacle for their potential to be developed further as a part of an engineering-oriented, modelling tool. This is

because intelligently populating a GIS-based or similar system for high-level engineering analysis requires three things: (1) collecting data in a manner that is timely, cost-efficient, and inherently compatible with the existing underlying system, (2) obtaining data of sufficient accuracy and detail that the resulting information is meaningful to the end user, and (3) manipulating, coding, and archiving the data in a format that critical information can be extracted as relevant input parameters to conduct engineering analyses. The advent of new remote sensing capabilities opens the door to meeting these challenges.

New opportunities in remote sensing data capture

Light Detection and Ranging (LiDAR) is an active remote sensing technology used to collect topographical data [64]. For the aerial version, the data are collected with aircraft-mounted lasers capable of recording elevation measurements at a rate of 5,000-50,000 pulses/sec. The difference in time is measured from when a laser pulse is emitted from a sensor to when the target objects in the path of the laser reflect back the pulse. Using the speed of light, these time measurements can be converted into distance or range [65]. The LiDAR instruments collect elevation data. To make these data spatially relevant, the points' positions must be known. Thus, a high-precision global positioning system (GPS) antenna, mounted on the aircraft, is used to determine the spatial position of each data point. The end product is accurate, geographically registered positions for every data point with respect to longitude, latitude, and elevation from mean sea level (x, y, z) and is typically presented in a plane coordinate system [66]. The terrestrial version of LiDAR uses essentially the same technology but is acquired from the ground with either a stationary or truck-mounted unit.

LiDAR is capable of providing both horizontal and vertical information at high spatial resolutions and vertical accuracies. In general, airborne-based LiDAR data can be within centimetre accuracy and the terrestrial sub-millimetre depending upon the distance, scanning period, and hardware. The extent of aerial LiDAR point density depends on flying height and system dependent factors such as platform velocity, sampling frequency, and field of view [67, 68, and 69]. LiDAR has been used in many applications such as (a) mapping, (b) forestry, (c) coastal engineering, (d) flood plain mapping, (e) disaster damage assessment and response, and (f) urban modelling. A current limitation of LiDAR is that it does not store any topological, shape, or size information of the geographical features scanned. A LiDAR dataset is simply a collection of somewhat randomly distributed 3D points. As it does not

provide feature information, clever and efficient algorithms are required for element identification depending upon the desired application. Furthermore, attributes must be assigned to groups of points to enable analysis. Recent advances in flight path planning and hardware have radically improved the resolution, as shown in Fig. 8 [70].

(a) LiDAR from a conventional, single path flyover in Dublin study area

(b) LiDAR from a multi-path swath flyover in Dublin study area

Figure 8: Comparison of conventional flight path resolution versus employing techniques developed in Hinks et al. [70].

Divergence

To properly envision the population, construction, and ultimate usage of a large-scale computational urban model, there must first be an understanding of the comparative needs of this type of system versus the previously described virtual cities and visualisation-based, urban-scale models. In a visual model, there may be a great emphasis on architectural details, colour, shading, and texture. Even the surface degradations caused by pollution, rust-staining, efflorescence, plant decay, and wind erosion may be of great importance to be captured to adequately convey the feel of an environment (Table 4). Additionally, building signage, window trimmings in the form of curtains and shades, and other non-structural façade elements may play a crucial role to make an environment appear realistically inhabited. But in the same way that street furniture (i.e. benches, trash bins, and railings), rarely influence engineering assessments and decisions, their absence would leave a visual rendition of an urban environment less convincing. Thus, in the context of a visual model, their importance must be respected, but their absence in an engineering context should not be confused as a deficit in that model. In fact, the converse is most likely true as computational models must in part be considered for their speed and computing needs. In current applications, it is not unusual for the run-time for a single large structure to need to be left overnight. As such, when considering city-scale computational modelling and the requisite computing power, it would appear to be absolutely crucial that extraneous (or at least non-critical) items be

excluded.

Table 5: Comparison of the needs of visualisation-based and computationally-based urban models

Consideration	Visualisation-based	Computationally-based	Commonality
Attractiveness	High priority	Not applicable	None
Shading	High priority	Not applicable	None
Window identification	High priority	High priority	High
Colour	Medium priority	Not applicable	None
Texture	Medium priority	Not applicable	None
Architectural details	Medium priority	Low priority	Medium
Building signage	Medium priority	Not applicable	None
Vegetation	Medium priority	Not applicable	None
Street furniture	Medium priority	Low priority*	Low
Vehicles	Low priority	Not applicable	None
Spatial accuracy	Low priority	High priority	Low
Material identification	Low priority	High priority	Low
Structural feature identification	Not applicable	High priority (somewhat application dependent)	None
Mutability	Not applicable	High priority	None

*Of some significance during high explosives based blast modelling as these object may become projectiles

Of the 14 items listed in Table 5 as possible characteristics or feature content for urban-scale models, nearly two-thirds of them have no commonality between visual and engineering models. Of the other 5 topics, 3 have a low commonality, 1 a medium commonality, and only window detection is of high mutual importance.

What may be difficult to understand at a visceral level is that an urban model may have great functionality without being visually compelling and that the converse is also true. Namely that although an image may have great visual appeal and be highly realistic in all of its aspects, it may have limited, if any, capabilities from an engineering perspective. Presently, the functionality of most virtual or visualisation models is limited to ray tracing activities, which may be useful for such topics as determining cell phone reception. This is not to say that eventually the two concepts may not be completely aligned, but that for the present there is a major disconnect that needs to be acknowledged.

Bottlenecks

Current bottlenecks to generating urban-scale computational models are in large part related the cost of populating such systems with relevant, geo-spatially accurate data. A major challenge is in the automatic identification of individual structures without any a priori

knowledge. Although readily identifiable to the human eye, the required data segregation by building without using known building outlines or other means a priori means has proven problematic. Recent efforts by Hinks et al. [70] indicate the strong potential to do this in the near future with a high level of reliability through LiDAR data (Fig. 9).

Fig. 9: Comparison of the results of traditional techniques versus work in progress techniques by Hinks et al. [70] for automatic building identification, with results evident by the flood-filled structures.

The LiDAR data outlined in the previous section is not a panacea. It cannot capture the interior of structures, nor identify the sizing and exact positioning of structural members, nor categorize the construction materials. However the existing technology could provide a major cost-savings in terms of identifying the position, outline, and major features of the buildings, and in those respects is no different than the role of the traditional survey team sent to document existing structures in-situ.

Discussion

What is envisioned is a pipeline using remote sensing to automatically and seamlessly to generate neutral files that can be read by commercial computational modelling programmes to generate solid models that converge without any further intervention and generate reasonable results on a city-scale. The fundamentals of such a pipelines are depicted in Fig. 10. These encompass only the items listed as high priority for computational modelling in Table 5.

Fig. 10: LiDAR processing from terrestrial point cloud data into a commercial programme's solid model [71]

Conclusions

In this study, recently published strategies for the creation and population of urban microclimate models have been reviewed in the context of physical and numerical modelling for air quality, wind environments, and urban heat islands. The trends showed a predominance for numerical modelling with the study area covered by different authors varying from single buildings to entire city sections. The scale used in modelling ranged from 1:20 to 1:1000. The standard k- ϵ model was most widely used model, and Fluent was mostly commonly applied commercial code. In numerical modelling researchers used a wide range of computational domains, number of grids, element types, and convergence criteria. In physical modelling different wind directions and number of point for readings were variously selected. This paper outlines the fundamental incompatibility between existing urban-scale models developed for visualisation and those that will be increasingly needed for computational modelling in the twenty-first century. The critical characteristics required for these future systems are introduced and a portion of the required pipeline to achieve this in an entirely automated manner is introduced using aerial LiDAR as the main component of its input data.

ACKNOWLEDGMENTS

Thanks to Dr. Agota Szucs and Ms. Orlaith O'Brien who helped during the early stages of this work. Also thanks to the authors of the research articles who provided extra information wherever it was needed. Support for this work was generously provided by Science

Foundation Ireland, Grant 05/PICA/I830 and the Environmental Protection Agency Grant 2005-CD-U1-M1.

REFERENCES

- [1] Okeil, A. “A holistic approach to energy efficient building forms”. *Energy and Buildings* 2009; 42(9): 1437-1444.
- [2] Han J, Yang W, Zhou J, Zhang G, Zhang Q, Moschandreas DJ. A comparative analysis of urban and rural residential thermal comfort under natural ventilation environment. *Energy and Buildings* 2009; 41(2): 139-145.
- [3] Kantzioura P, Kosmopoulos S, Zoras S. Urban surface temperature and microclimate measurements in Thessaloniki. *Energy and Buildings* 2012; 44(1): 63-72.
- [4] Stazi F, Di Perna C, Munafò P. Durability of 20-year-old external insulation and assessment of various types of retrofitting to meet new energy regulations. *Energy and Buildings* 2009; 41(7): 721-731.
- [5] Martinaitis V, Biekša D, Miseviciute V. Degree-days for the exergy analysis of buildings. *Energy and Buildings* 2010; 42 (7): 1063-1069.
- [6] Cheng WC, Liu CH, Leung DYC. On the correlation of air and pollutant exchange for street canyons in combined wind-buoyancy-driven flow. *Atmospheric Environment* 2009; 43: 3682-90.
- [7] Kim K, Kim K, Kim BS. A wind tunnel experiment and CFD analysis on airflow performance of enclosed-arcade markets in Korea. *Building and Environment* 2009; 45: 1329-38.
- [8] Szucs A, Moreau S, Allard F. Spectators’ aerothermal comfort assessment method in stadia”. *Building and Environment* 2007; 42: 2227-40.
- [9] Yoshie R, Mochida A, Tominaga Y, Kataoka H, Yoshikawa M. Cross Comparisons of CFD Prediction for Wind Environment at Pedestrian Level around Buildings. Sixth Asia-Pacific Conference on Wind Engineering (APCWE-VI) Seoul Korea, 12-14 September 2005.
- [10] Agarwal M, Tandon A. Modeling of the urban heat island in the form of mesoscale wind and of its effect on air pollution dispersal. *Applied Mathematical Modelling* 2009; 34: 2520-30.
- [11] McNabola A, Broderick BM, Gill LW. A numerical investigation of the impact of low boundary walls on pedestrian exposure to air pollutants in urban street canyons. *Science of the Total Environment* 2008; 407: 760-69.
- [12] Priyadarsini R, Hien WN, David CKW. Microclimatic modeling of the urban thermal environment of Singapore to mitigate urban heat island. *Solar Energy* 2008; 82: 727-45.

- [13] Gromke C, Buccolieri R., Di S S, Ruck B. Dispersion study in a street canyon with tree planting by means of wind tunnel and numerical investigations–Evaluation of CFD data with experimental data. *Atmospheric Environment* 2008; 42: 8640-50.
- [14] McNabola A, Broderick BM, Gill LW. The impacts of inter-vehicle spacing on in-vehicle air pollution concentrations in idling urban traffic conditions. *Transportation Research Part* 2009; D 14: 567-75.
- [15] Alexandri E, Jones P. Temperature decreases in an urban canyon due to green walls and green roofs in diverse climates. *Building and Environment* 2008; 43: 480-93.
- [16] Huang Y, Hu X, Zeng N. Impact of wedge-shaped roofs on airflow and pollutant dispersion inside urban street canyons”. *Building and Environment* 2009; 44: 2335–2347.
- [17] He J, Hoyano A, Asawa T. A numerical simulation tool for predicting the impact of outdoor thermal environment on building energy performance. *Applied Energy* 2009; 86: 1596-1605.
- [18] Abuku M, Blocken B, Nore K, Thue JV, Carmeliet J, Roels S. On the validity of numerical wind-driven rain simulation on a rectangular low-rise building under various oblique winds. *Building and Environment* 2008; 44: 621-632.
- [19] Blocken B, Carmeliet J. Overview of three state-of-the-art wind-driven rain assessment models and comparison based on model theory. *Building and Environment* 2009; 45: 691-703.
- [20] Carpentieri M, Robins AG. Wind tunnel experiments of flow and dispersion in a real urban area. *The Seventh International Conference on Urban Climate*, 29 June - 3 July 2009, Yokohama, Japan.
- [21] Cheng WC, Liu CH, Leung DY. Computational formulation for the evaluation of street canyon ventilation and pollutant removal performance. *Atmospheric Environment* 2008; 42: 9041-51.
- [22] Coirier WJ, Fricker DM, Furmanczyk M, Kim S. A Computational Fluid Dynamics Approach for Urban Area Transport and Dispersion Modeling. *Environmental Fluid Mechanics* 2005; 5: 443-79.
- [23] Hooff TV, Blocken B. Coupled urban wind flow and indoor natural ventilation modelling on a high-resolution grid: A case study for the Amsterdam Arena stadium. *Environmental Modelling & Software* 2009; 25: 51-65.
- [24] Hooff TV, Blocken B. On the effect of wind direction and urban surroundings on natural ventilation of a large semi-enclosed stadium. *Computers & Fluids* 2010; 39: 1146-55.
- [25] Hua CH, Wang F. Using a CFD approach for the study of street-level winds in a built-up area. *Building and Environment* 2005; 40: 617-31.

- [26] Huang Y, Hu X, Zeng N. Impact of wedge-shaped roofs on airflow and pollutant dispersion inside urban street canyons. *Building and Environment* 2009; 44: 2335-47.
- [27] Huang JM, Ooka R, Okada A, Omori A, Huang H. The effects of urban heat island mitigation strategies on the outdoor thermal environment in central Tokyo – a numerical simulation. *The seventh Asia-pacific conference on wind engineering*. Taiwan: Taipei; 2009.
- [28] Huang H, Ooka H, Kato S. Urban thermal environment measurements and numerical simulation for an actual complex urban area covering a large district heating and cooling system in summer. *Atmospheric Environment* 2005; 39: 6362-75.
- [29] Li K, and Yu Z. Comparative and Combinative Study of Urban Heat Island in Wuhan City with Remote Sensing and CFD Simulation. *Sensors* 2008; 8: 6692-6703.
- [30] Memon RA, Leung DY, Liu CH. Effects of building aspect ratio and wind speed on air temperatures in urban-like street canyons. *Building and Environment* 2009; 45: 176-88.
- [31] Meyn SK, Oke TR. Heat fluxes through roofs and their relevance to estimates of urban heat storage. *Energy and Buildings* 2009; 41: 745-52.
- [32] Neofytou P, Venetsanos AG, Vlachogiannis D, Bartzis JG, Scaperdas A. CFD simulations of the wind environment around an airport terminal building. *Environmental Modelling & Software* 2006; 21: 520-24.
- [33] Oguro M, Morikawa Y, Murakami S, Matsunawa K, Mochida A, Hayashi H. Development of a wind environment database in Tokyo for a comprehensive assessment system for heat island relaxation measures. *Journal of Wind Engineering and Industrial Aerodynamics* 2008; 96: 1591-1602.
- [34] Oliveria P, Goncalves HJP, Ferrao PMC. Numerical analysis of the street canyon thermal conductance to improve urban design and climate. *Building and Environment* 2009; 44: 177-87.
- [35] Oxizidis S, Dudek AV, Papadopoulos AM. A computational method to assess the impact of urban climate on buildings using modeled climatic data. *Energy and Buildings* 2008; 40: 215-23.
- [36] Parra MA, Santiago JL, Martín F, Martilli A, and Santamaría JM. A methodology to urban air quality assessment during large time periods of winter using computational fluid dynamic models. *Atmospheric Environment* 2010; 44: 2089-97.
- [37] Sabatino SD, Buccolieri R, Pulvirenti B, Britter RE. Flow and Pollutant Dispersion in Street Canyons using FLUENT and ADMS-Urban. *Environ Model Assess* 2008; 13: 369-81.
- [38] Sato T, Murakami S, Ooka R, Yoshida S. Analysis of regional characteristics of the atmospheric heat balance in the Tokyo metropolitan area in summer. *Journal of Wind Engineering and Industrial Aerodynamics* 2008; 96: 1640-54.
- [39] Shashua-Bar L, Pearlmutter D, Erell E. The cooling efficiency of urban landscape strategies in a hot dry climate. *Landscape and Urban Planning* 2009; 92: 179-86.

- [40] Short CA, Cook MJ, Woods A. Low energy ventilation and cooling within an urban heat island. *Renewable Energy* 2009; 34: 2022-29.
- [41] Tewari M, Kusaka H, Chen F, Coirier WJ, Kim S, Wyszogrodzki AA, Warner TT. Impact of coupling a microscale computational fluid dynamics model with a mesoscale model on urban scale contaminant transport and dispersion. *Atmospheric Research* 2010; 96: 656-64.
- [42] Wakes S J, Maegli T, Dickinson KJ, Hilton MJ. Numerical modelling of wind flow over a complex topography. *Environmental Modelling & Software* 2009; 25: 237-47.
- [43] Wang P. and Mu H. Numerical simulation of pollutant flow and dispersion in different street layouts. *International Journal of Environmental Studies* 2010; 67(2): 155-67.
- [44] Xiao-min X, Jia-song W, Zhen H. Traffic emission transportation in street canyons. *Journal of Hydrodynamics* 2008; 21(1): 108-17.
- [45] Yassin MF, Kellnerova R, Janour Z. Impact of street intersections on air quality in an urban environment. *Atmospheric Environment* 2008; 42: 4948-63.
- [46] Zhang A, Gao C, Zhang L. Numerical simulation of the wind field around different building arrangements. *Journal of Wind Engineering and Industrial Aerodynamics* 2005; 93: 891-904.
- [47] Dobbyn S, Hamill J, O’Conor K, O’Sullivan C. Geopostors: A Real-Time Geometry/Impostor Crowd Rendering System. *Proceedings of the ACM SIGGRAPH Symposium on Interactive 3D Graphics and Games*. Washington D.C; 2005: 95-102.
- [48] <http://www.mayo-ireland.ie/virtualtours/westport.htm>.
- [49] Parish Y, and Müller P. Procedural Modelling of Cities. *Computer Graphics, Proc. SIGGRAPH’2001*: 301-308.
- [50] Watson B, Müller P, Wonka P, Sexton C, Veryovka O, and Fuller A. Procedural Urban Modeling in Practice. *Procedural Methods for Urban Modeling Tutorial IEEE Computer Graphics and Applications*, May/June 2008: 18-26.
- [51] Wonka P, Wimmer M, Sillion F, and Ribarsky W. Instant Architecture. *ACM Transactions on Graphics* 2003; 22(3): 669-77.
- [52] Maas HG and Vosselman G. Two Algorithms for Extracting Building Models from Raw Laser Altimetry Data. *ISPRS Journal of Photogrammetry and Remote Sensing* 1999; 54(2-3): 153-63.
- [53] Jepson W, Liggett R, Friedman S. Virtual Modelling of Urban Environments. *Presence* 1996; 5(1): 83-95.
- [54] <http://usa.autodesk.com/adsk/servlet/index?siteID=123112&id=565930232> texture warping.

- [55] Debevec PE, Taylor CJ, Malik J. Modelling and Rendering Architecture from Photographs: A Hybrid Geometry- and Image-based Approach. *Computer Graphics; Proc. SIGGRAPH 1996*; 96: 11-20.
- [56] Teller S. MIT CSAIL MIT City Scanning Project, 2005, www.city.lcs.mit.edu/city.html.
- [57] Coorg S, *Pose Imagery and Automated Three-Dimensional Modeling of Urban Environments*, PhD thesis, MIT, 1998.
- [58] Wang X, Totaro S, Taillandier G, Hanson A., and Teller S. Recovering Façade Texture and Microstructure from Real-World Images. *Proc. 2nd International Workshop on Texture Analysis and Synthesis 2002*; 145-149.
- [59] Teller S. *Visibility Computation in Densely Occluded Polyhedral Environments*, PhD thesis, Computer Science Department, UC Berkeley, 1992.
- [60] Lee SC, Jung SK, and Nevatia R. Automatic integration of façade textures into 3D building models with a projective geometry based line clustering. *Computer Graphics Forum 2002*; 21(3): 677-86.
- [61] Sun J, Baciú G, Yu X, and Green M. Template-based Generation of Road Networks for Virtual City Modelling. *Proc. ACM VRST, 2002*; 33-40.
- [62] Yap C, Bierman H, Hertzman A, Li C, Meyer J, Pao HK, and Paxia TA. A Different Manhattan project: Automatic statistical model generation. *Proc. SPIE Visualization and Data Analysis 2002*; 259-68.
- [63] Laycock RG, and Day AM. Automatically Generating Large Urban Environments Based on the Footprint Data of Buildings. *SM'03: Proceedings of the 8th ACM Symposium on Solid Modelling and Applications, 2003*; 346-51.
- [64] Van Veen HA, Distler HC, Distler HK, Braun SJ, Bühlhoff HH. Navigating through a Virtual City: Using Virtual Reality Technology to Study Human Action and Perception. *Future Generation Computer Systems 1998*; 14(3-4): 231-42.
- [65] NOAA 2003 About LIDAR Data
<http://www.csc.noaa.gov/products/sccoasts/html/tutlid.htm>
- [66] Lim K, Treitz P, Groot A and St-Onge B. Estimation of Individual Tree Heights Using LiDAR Remote Sensing. *Proceedings of the 23rd Canadian Symposium on Remote Sensing. Canadian Aeronautics and Space Institute, Ottawa 2001*: 251-258.
- [67] Axelsson P. Processing of Laser Scanner Data – Algorithms and Applications. *ISPRS Journal of Photogrammetry and Remote Sensing 1999*; 54(2-3): 138-47.
- [68] Baltsavias M. Airborne Laser Scanning- Basic Relations and Formulas. *ISPRS Journal of Photogrammetry and Remote Sensing 1999*; 54(2-3): 199-214.

[69] Airborne-lasermapping '03 Overview - An Emerging Survey Technology
<http://www.airbornelaser-mapping.com/ALMSkinny.html>

[70] Hinks T, Carr H, Laefer DF. "Flight Optimization Algorithms for Aerial LiDAR Capture for Urban Infrastructure Model Generation. Journal of Computing in Civil Engineering 2009; 23(6): 330-9.

[71] Truong-Hong L. Automatic generation of solid models from LiDAR data. Ph.D. Thesis. University College Dublin, Ireland, 2011.